

**Jamson Labs**

Quality Chemicals Since 1973

Directions:

- Use to prepare silkscreens prior to setting emulsion and burning image.
- Apply liberally to both sides of the silkscreen and allow to react for 5 minutes.
- Rinse thoroughly and dry before setting emulsion.
- Dilute 1 part to 3 parts water to dehaze screens.

DANGER:

DO NOT TAKE INTERNALLY. HARMFUL IF INHALED OR SWALLOWED.

CAUTION: KEEP OUT OF REACH OF CHILDREN.

MAY CAUSE HARM TO PAINTED SURFACES IF NOT USED AS DIRECTED

Screen Prep & Degreaser

INDUSTRIAL-GRADE FORMULATION

- SAFELY AND QUICKLY
CLEANS AND DEGREASES

 1 Gal. 5 Gal. 55 Gal. 275 Gal.**TRANSPORT INFORMATION:**

Proper Shipping Name -
Corrosive Liquids, N.O.S.,
(Contains Potassium Hydroxide)
DOT Hazard Class - 8 Packing Group - III
ID# - UN 1760

Inhalation: Remove affected person to fresh air; wash mouth and nasal passages with water repeatedly; if breathing difficulties persist seek medical attention.

Skin: Remove contaminated clothing; wash affected area with soap and water; DO NOT attempt to neutralize with chemical agents; if irritation persists, seek medical attention. Launder contaminated clothing before reuse.

Eyes: Check for and remove any contact lenses. Immediately flush eyes with clear running water for 15 minutes while holding eyelids open. Seek medical attention immediately.

Ingestion: Drink two glasses of water followed by milk; give diluted vinegar or lemon juice to conscious person; DO NOT induce vomiting; seek medical attention immediately.

**Jamson Labs**

Quality Chemicals Since 1973

Jamson Laboratories Inc.

(813) 855-4565

FAX (813) 854-3133

In Case Of Chemical Emergency Contact

Chem-Tel 24 Hours (800) 255-3924