Printing date 10/31/2014

Reviewed on 06/25/2014


1 Identification	
 Product identifier Trade name: <u>Heavy Duty Floor Cleaner</u> Article number: 0813 PK Details of the supplier of the safety data sheet 	Jamson Labs Power Kleen Chemical Solutions Since 1973
• <i>Manufacturer/Supplier:</i> Power Kleen Corporation 101 South Bayview Blvd. OLDSMAR, FL 34677 USA	
• Information department: Product Safety Department • Emergency telephone number: ChemTel Inc. (800)	nt 255-3924 Intl. +01 (813) 248-0585
2 Hazard(s) identification	
Classification of the substance or mixture	
Skin Corr. 1B H314 Causes severe skin burns and • Label elements • GHS label elements The product is classified and la • Hazard pictograms	beled according to the Globally Harmonized System (GHS).
GHS05 • Signal word Danger	
 Hazard-determining components of labeling: disodium metasilicate Hazard statements Causes severe skin burns and eye damage. Precautionary statements 	
	or label at hand. all contaminated clothing. Rinse skin with water/shower. al minutes. Remove contact lenses, if present and easy to do.
Store locked up. Dispose of contents/container in accordance with lo	cal/regional/national/international regulations. (Contd. on page 2) USA

Printing date 10/31/2014

Reviewed on 06/25/2014

Trade name: Heavy Duty Floor Cleaner

(Contd. of page 1)



 $\begin{array}{c} \mathbf{0} \\ \mathbf{0} \\ \mathbf{3} \\ \mathbf{0} \end{array} \begin{array}{c} Health = 3 \\ Fire = 0 \\ Reactivity = 0 \end{array}$

· HMIS-ratings (scale 0 - 4)

HEALTH3Health = 3FIRE0Fire = 0REACTIVITY0Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous o	components:	
111-76-2	2-butoxyethanol	10-25%
6834-92-0	disodium metasilicate	2.5-10%
66455-15-0	C10-12 6 Mole Linear Alcohol Ethoxylate	2.5-10%

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Remove contact lenses if able to do so.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

• Most important symptoms and effects, both acute and delayed

Corrosive and extremely irritating to all tissues. Nausea

Gastric or intestinal disorders

Cramp

· **Danger** Danger of gastric perforation.

(Contd. on page 3)

USA

Printing date 10/31/2014

Reviewed on 06/25/2014

Trade name: Heavy Duty Floor Cleaner

• Indication of any immediate medical attention and special treatment needed Medical supervision for at least 48 hours.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture Carbon monoxide (CO)
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- *Environmental precautions: Dilute with plenty of water.*
- Do not allow to enter sewers/ surface or ground water.
- \cdot Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent.
- Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.
- **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility:
- Store away from oxidizing agents. Store away from foodstuffs.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

USA

(Contd. of page 2)

Printing date 10/31/2014

Reviewed on 06/25/2014

Trade name: Heavy Duty Floor Cleaner

(Contd. of page 3)

· Cont	rol parameters			
· Com	· Components with limit values that require monitoring at the workplace:			
111-1	111-76-2 2-butoxyethanol			
PEL	Long-term value: 240 mg/m ³ , 50 ppm Skin			
REL	Long-term value: 24 mg/m³, 5 ppm Skin			
TLV	Long-term value: 97 mg/m³, 20 ppm BEI			
· Ingro	edients with biological limit values:			
111-1	76-2 2-butoxyethanol			
BEI	200 mg/g creatinine			
	Medium: urine			
	Time: end of shift			
	Parameter: Butoxyacetic acid with hydrolysis			
· Addi	tional information: The lists that were valid during the creation were used as basis.			
· Expo	osure controls			
	onal protective equipment:			
	ral protective and hygienic measures:			
	away from foodstuffs, beverages and feed.			
Imme	ediately remove all soiled and contaminated clothing.			
Wash	n hands before breaks and at the end of work.			
Avoi	d contact with the eyes and skin.			
	thing equipment:			
respi	se of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use ratory protective device that is independent of circulating air.			
· Prote	ection of hands:			

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves

Neoprene gloves PVC or PE gloves Nitrile rubber, NBR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

(Contd. on page 5)

USA

(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/31/2014

Reviewed on 06/25/2014

Trade name: Heavy Duty Floor Cleaner

• *Body protection:* Alkaline resistant protective clothing

Physical and chemical proper	lles	
Information on basic physical and	chemical properties	
General Information		
Appearance:		
Form:	Liquid	
Color:	Amber colored	
Odor:	Characteristic	
Odour threshold:	Not determined.	
<i>pH-value at 20 °C (68 °F):</i>	12.9	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	240 °C (464 °F)	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	1.1 Vol %	
Upper:	10.6 Vol %	
Vapor pressure:	Not determined.	
Density at 20 °C (68 °F):	1 g/cm ³ (8.345 lbs/gal)	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/wat	er): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	12.5 %	
Water:	75.4 %	
VOC content:	12.5 %	
	139.7 g/l / 1.17 lb/gl	
Solids content:	12.1 %	
Other information	No further relevant information available.	

(Contd. on page 6)

Printing date 10/31/2014

Reviewed on 06/25/2014

Trade name: Heavy Duty Floor Cleaner

(Contd. of page 5)

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Reacts with strong acids and oxidizing agents.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:
- Sulfur oxides (SOx) Sodium Oxides Carbon monoxide and carbon dioxide

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

111-76-2 2-butoxyethanol

Oral LD50 1480 mg/kg (rat)

Dermal LD50 400 mg/kg (rab)

6834-92-0 disodium metasilicate

Oral LD50 1280 mg/kg (rat)

- · Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye: Strong caustic effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
111-76-2 2-butoxyethanol	3
67-63-0 propan-2-ol	3
· NTP (National Toxicology Program)	
None of the ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	

None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic toxicity: No further relevant information available.

- *Persistence and degradability No further relevant information available.*
- · Bioaccumulative potential No further relevant information available.

Printing date 10/31/2014

Reviewed on 06/25/2014

Trade name: Heavy Duty Floor Cleaner

(Contd. of page 6)

- *Mobility in soil* No further relevant information available.
- \cdot Additional ecological information:
- · General notes:
- Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even extremely small quantities leak into the ground.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number	
DOT	Not regulated
· UN proper shipping name	
· DOT	Not regulated
• Transport hazard class(es)	
DOT	Not applicable
Packing group	
· DOT	Not applicable
Environmental hazards:	
Marine pollutant:	No
Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	Not regulated DOT (USA) ground only, non-bulk <120gals.
· UN "Model Regulation":	UN3082, Environmentally hazardous substances, liquid, n.o.s. (N. 9 (4-nonyl phenol 9 mole E.O.)), 9, III

(Contd. on page 8)

Printing date 10/31/2014

Reviewed on 06/25/2014

Trade name: Heavy Duty Floor Cleaner

(Contd. of page 7)

· Safety, healt · Sara	h and environmental regulations/legislation specific for the substance or mixture	
	(extremely hazardous substances):	
	ingredients is listed.	
Section 313	(Specific toxic chemical listings):	
	butoxyethanol	
67-63-0 pr	•	
TSCA (Toxi	c Substances Control Act):	
	2-butoxyethanol	
6834-92-0	disodium metasilicate	
66455-15-0	C10-12 6 Mole Linear Alcohol Ethoxylate	
1300-72-7	sodium xylenesulphonate	
64-02-8	tetrasodium ethylenediaminetetraacetate	
	propan-2-ol	
	water, distilled, conductivity or of similar purity	
Proposition		
Chemicals k	nown to cause cancer:	
None of the i	ingredients is listed.	
Chemicals k	nown to cause reproductive toxicity for females:	
None of the i	ingredients is listed.	
Chemicalski	nown to cause reproductive toxicity for males.	
None of the i	ingredients is listed.	
Chemicals k	nown to cause developmental toxicity:	
None of the i	ingredients is listed.	
Carcinogeni	c categories	
-	onmental Protection Agency)	
111-76-2 2-	butoxyethanol	N
TLV (Thresh	hold Limit Value established by ACGIH)	I
,	butoxyethanol	A
67-63-0 pr		A

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

• *Hazard-determining components of labeling: disodium metasilicate*

(Contd. on page 9)

USA

US 4

Safety Data Sheet acc. to OSHA HCS

Printing date 10/31/2014

Reviewed on 06/25/2014

Trade name: Heavy Duty Floor Cleaner

Contd. of page 8) • Hazard statements Causes severe skin burns and eye damage. • Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Do not breathe dust/fume/gas/mist/vapours/spray. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see on this label). Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. • Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing MSDS: Environment protection department.

Date of preparation / last revision 10/31/2014 / Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B