

**Jamson Labs**

Quality Chemicals Since 1973

Directions:

- Apply a small amount on a scrub brush or sponge and agitate to remove stubborn stains.

HANDLING & STORAGE

Vapors of product are heavier than air and will collect in low areas such as pits, degreasers, storage tanks, and other confined areas. Do not enter these areas where vapors or Methylene Chloride are suspected unless special breathing apparatus is used and observer is present for assistance.

Liquid and vapor of this product can decompose to harmful and corrosive vapors when in contact with flame and other ignition sources. In addition, this product may develop a flammable atmosphere in confined areas. **KEEP AWAY FROM FLAMES AND OTHER IGNITION SOURCES**, such as welding, when used where vapors may become concentrated. **DO NOT CUT OR WELD CONTAINER** due to explosion hazard. **FOR SPILLS**, use proper protective

equipment. For small spills use sorbent, allow to stand, then sweep into airtight container for disposal. For large spills, evacuate the area, dike, then pump into containers for disposal.

NOTE: This product repacked for consumer markets may require labeling different than give on this container.

INHALATION PRECAUTIONS:

High concentrations of vapors can accumulate in low areas. Progressively higher exposure levels over 1000 ppm can cause dizziness, drunkenness, unconsciousness or even **DEATH**. **EXTREMELY** high vapor concentrations (over 10,000 ppm) are immediately **HAZARDOUS TO LIFE**. **CONTINUED EXPOSURE SHOULD NOT EXCEED OSHA 8-HOUR TWA**. Repeated and prolonged exposure to vapor concentrations at or above where physical effects begin (dizziness, eye irritation) may be hazardous to health.

EXPOSURE LIMITS-PARTS PER MILLION (PPM) OSHA: 8-HOUR TWA: 500 PPM

DANGER:

DO NOT TAKE INTERNALLY. HARMFUL IF INHALED OR SWALLOWED.

CAUTION: KEEP OUT OF REACH OF CHILDREN.

Cable Cleaner

HIGH VOLTAGE CLEANER & DEGREASER

INDUSTRIAL STRENGTH FORMULATION

- **POWERFUL LIQUID CLEANER FOR USE ON ELECTRICAL CABLES, SWITCHGEAR, PCBs AND OVERHEAD POWER LINES**
- **FORMULATED TO A HIGH DIELECTRIC STRENGTH OF 50,000V AND DESIGNED SPECIFICALLY TO REMOVE GREASES, CABLE JELLY, BITUMEN, SEALANTS AND OILS WITHOUT AFFECTING INSULATION OR CABLE CORES**
- **ALSO GOOD FOR POWER CABLES FOR BOATS AND DOCKS**

 1 Gal. 5 Gal. 55 Gal. 275 Gal.**TRANSPORT INFORMATION:**

Proper Shipping Name - Dichloromethane Mixture
DOT Hazard Class - 6.1
Packing Group - PG III
ID# - UN 1593

Inhalation: Remove affected person to fresh air; if not breathing, administer CPR and seek medical attention.

Skin: Remove contaminated clothing; wash affected area with soap and water; DO NOT attempt to neutralize with chemical agents; if irritation persists, seek medical attention. Launder contaminated clothing before reuse.

Eyes: Check for and remove any contact lenses. Immediately flush eyes with clear running water for 15 minutes while holding eyelids open. Seek medical attention immediately.

Ingestion: Drink two glasses of water to conscious person; DO NOT induce vomiting; seek medical attention immediately.

**Jamson Labs**

Quality Chemicals Since 1973

Jamson Laboratories Inc.

(813) 855-4565

FAX (813) 854-3133

In Case Of Chemical Emergency Contact
Chem-Tel 24 Hours (800) 255-3924