

Super Slick

 - Tar/Asphalt Lubricant/Protectant

PRODUCT #: JL-1000

CHARACTERISTICS:

Appearance:	Clear liquid
Odor:	Solvent
pH:	N/A
Specific Gravity	0.820
Weight	6.84
Viscosity	Water Like
Flash Point	140
Dilution	1:40

ADVANTAGES:

Product is an industrial-grade concentrate and a stable, complex blend of oils, emulsifying agents and heat resistant release agents designed to coat and prevent adhesion to all surfaces that may come in contact with asphalt. Super Slick is for use in setting free asphalt which may come in contact with truck beds.

DIRECTIONS:

Only 1 gallon is used to 40 gallons of water. This will provide a high lubricity foam shield which prevents adhesion of asphalt to truck beds and sides.

PRECAUTIONS:

Inhalation: Remove affected person to fresh air; if symptoms persist seek medical attention.

Skin: Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

Eyes: Check for and remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

Ingestion: Give two glasses of water for dilution; DO NOT induce vomiting; never give anything by mouth to an unconscious person; seek medical attention.

TRANSPORT INFO:

Proper Shipping Name - Not Regulated for Transport by Truck

DOT Hazard Class - Not Regulated

Packing Group - Not Regulated

ID# - Not Regulated



AVAILABLE IN:

Gal. Jug, 5 Gal. Bucket, 55 Gal. Drum,
275 Gal. Tote, 300 Gal. Leg Tank or delivered via Tanker Truck



GUARANTEE: Jamson Labs' / Power Kleen's manufacturing and laboratory controls ensure uniform quality throughout our product line. All Jamson Labs / Power Kleen manufactured products are guaranteed for 1 year when used as directed.