


**Jamson Labs**

Quality Chemicals Since 1973

**Directions:**

- Only 1 gallon is used to 40 gallons of water.
- This will provide a high lubricity foam shield which prevents adhesion of asphalt to truck beds and sides.

# Super Slick

TAR/ASPHALT LUBRICANT/PROTECTANT

## Industrial-grade Concentrate

- **THIS PRODUCT IS A STABLE, COMPLEX BLEND OF OILS, EMULSIFYING AGENTS AND HEAT RESISTANT RELEASE AGENTS**
- **DESIGNED TO COAT AND PREVENT ADHESION TO ALL SURFACES THAT MAY COME IN CONTACT WITH ASPHALT**
- **FOR USE IN SETTING FREE ASPHALT WHICH MAY COME IN CONTACT WITH TRUCK BEDS**

1 Gal.  
  5 Gal.  
  55 Gal.  
  275 Gal.

THIS PRODUCT IS DESIGNED EXCLUSIVELY FOR INDUSTRIAL AND INSTITUTIONAL USE BY TRAINED PERSONNEL.

KEEP OUT OF REACH OF CHILDREN.

**Inhalation:** Remove affected person to fresh air; if symptoms persist seek medical attention.

**Skin:** Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

**Eyes:** Check for and remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

**Ingestion:** Give two glasses of water for dilution; DO NOT induce vomiting; never give anything by mouth to an unconscious person; seek medical attention.

**TRANSPORT INFORMATION:**

Proper Shipping Name - Not Regulated for Transport by Truck  
 DOT Hazard Class - Not Regulated  
 Packing Group - Not Regulated  
 ID# - None


**Jamson Labs**

Quality Chemicals Since 1973

Jamson Laboratories Inc.

(813) 855-4565

FAX (813) 854-3133

In Case Of Chemical Emergency Contact  
 Chem-Tel 24 Hours (800) 255-3924