
Printing date 11/06/2014 Reviewed on 06/26/2014

1 Identification

· Product identifier

· Trade name: Super Slick · Article number: 1000 JL



· Manufacturer/Supplier: Jamson Laboratories, Inc. 101 South Bayview Blvd. Oldsmar, FL 34677 USA



- · Information department: Product Safety Department
- Emergency telephone number: ChemTel Inc. (800) 255-3924 Intl. +01 (813) 248-0585

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

H227 Combustible liquid.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

- · Signal word Danger
- · Hazard statements

Combustible liquid.

Causes skin irritation.

Causes serious eye irritation.

May be fatal if swallowed and enters airways.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 2)

Printing date 11/06/2014 Reviewed on 06/26/2014

Trade name: Super Slick

(Contd. of page 1)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 2Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1 Fire = 2Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

66455-15-0 C10-12 6 Mole Linear Alcohol Ethoxylate

10-25%

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Remove contact lenses if able to do so.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

· Most important symptoms and effects, both acute and delayed

Nausea

Gastric or intestinal disorders

Dizziness

Headache

- · Danger Danger of disturbed cardiac rhythm.
- · Indication of any immediate medical attention and special treatment needed

Later observation for pneumonia and pulmonary edema.

Medical supervision for at least 48 hours.

(Contd. on page 3)

Printing date 11/06/2014 Reviewed on 06/26/2014

Trade name: Super Slick

(Contd. of page 2)

If swallowed or in case of vomiting, danger of entering the lungs.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture Carbon monoxide (CO)
- · Advice for firefighters
- · Protective equipment: Do not inhale explosion gases or combustion gases.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Protect from heat.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility:

Store away from oxidizing agents.

Store away from foodstuffs.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 4)

Printing date 11/06/2014 Reviewed on 06/26/2014

Trade name: Super Slick

(Contd. of page 3)

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Neoprene gloves

PVC or PE gloves

Nitrile rubber, NBR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Not determined.

- · Not suitable are gloves made of the following materials: Leather gloves
- · Eye protection:



Tightly sealed goggles

· **Body protection:** Solvent resistant protective clothing

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

· pH-value:

Form: Liquid

Color: Amber colored
Odor: Hydrocarbon
Odour threshold: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 175 °C (347 °F)

Flash point: 61 °C (142 °F)

· Flammability (solid, gaseous): Not applicable.

(Contd. on page 5)

Printing date 11/06/2014 Reviewed on 06/26/2014

Trade name: Super Slick

		(Contd. of page
· Ignition temperature:		
Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Not determined.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure:	Not determined.	
· Density at 20 °C (68 °F):	0.818 g/cm³ (6.826 lbs/gal)	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wa	ter): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	0.0 %	
Solids content:	100.0 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Reacts with oxidizing agents.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

(Contd. on page 6)

Printing date 11/06/2014 Reviewed on 06/26/2014

Trade name: Super Slick

(Contd. of page 5)

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT	Not regulated	
UN proper shipping name		
DOT	Not regulated	
Transport hazard class(es)		
DOT	Not applicable	
Packing group		
DOT	Not applicable	

(Contd. on page 7)

Printing date 11/06/2014 Reviewed on 06/26/2014

Trade name: Super Slick

(Contd. of page 6)

· Environmental hazards:

· Marine pollutant: No

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

66455-15-0 C10-12 6 Mole Linear Alcohol Ethoxylate

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicalsknown to cause reproductive toxicity for males.

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

- · Signal word Danger
- · Hazard statements

Combustible liquid.

Causes skin irritation.

Causes serious eye irritation.

May be fatal if swallowed and enters airways.

(Contd. on page 8)

Printing date 11/06/2014 Reviewed on 06/26/2014

Trade name: Super Slick

(Contd. of page 7)

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Environment protection department.
- · Date of preparation / last revision

11/06/2014 / -

6/26/2014

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

 $HMIS: Hazardous\ Materials\ Identification\ System\ (USA)$

 $: Flammable \ liquids, \ Hazard \ Category \ 4$

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

USA