

DIRECTIONS (General Use):

- Completely strip old finish.
(For best results, use PK-1250 Rinse No More)
- Rinse thoroughly with clear water and allow to air dry.
- Apply two to three (2-3) coats.
- For higher gloss, additional coats may be applied.
- Apply with a lambs wool applicator or a cotton mop.
- Always allow at least 30 minutes between coats.

Right Sheen 25

METAL INTERLOCKING FLOOR FINISH

HI-GLOSS SHINE (WITH 25% SOLIDS)

NON-BUFF / DURABLE / EFFECTIVE

- *DETERGENT WASHABLE*
- *EASILY REPAIRED*
- *MAINTAINS BRILLIANT GLOSS SHINE*

1 Gal.
 5 Gal.
 55 Gal.
 275 Gal.

Inhalation: Remove affected person to fresh air; if symptoms persist seek medical attention.

Skin: Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

Eyes: Check for and remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

Ingestion: Give two glasses of water for dilution; DO NOT induce vomiting; never give anything by mouth to an unconscious person; seek medical attention.

TRANSPORT INFORMATION:

Proper Shipping Name - Not Regulated for Transport by Truck
 DOT Hazard Class - Not Regulated
 Packing Group - Not Regulated
 ID# - None

PowerKleen

Quality Chemicals • Superior Service

Power Kleen Corporation

To Reorder, Call: (813) 854-2648

FAX (813) 854-3133

In Case Of Chemical Emergency Contact

Chem-Tel 24 Hours (800) 255-3924

www.PowerKleen.com