

PowerKleen
Quality Chemicals • Superior Service

Directions:

Spread generous solution on area to be stripped. Allow at least 10-15 minutes working time. Re-apply if necessary. DO NOT allow to dry on floor. Scrub with mop until finish is dissolved then wet vac or dry mop thoroughly. Rinse with clean water to remove all residue. Allow adequate time to completely dry before applying new finish.

DILUTION DIRECTIONS

HEAVIEST BUILDUP.....DILUTE 1-3

HEAVY BUILDUPDILUTE 1-5

NORMAL BUILDUPDILUTE 1-15

CAUTION KEEP OUT OF REACH OF CHILDREN.

DO NOT TAKE INTERNALLY. HARMFUL IF SWALLOWED.

AVOID CONTACT WITH EYES AND SKIN.

Finally

NON-AMMONIATED FLOOR FINISH STRIPPER

**DESIGNED TO REMOVE ALL WATER BASED
FLOOR FINISHES OR SEALERS, INCLUDING
METAL INTERLOCK — WITHOUT THE
NEED OF A FLOOR SCRUBBER.**

1 Gal. 5 Gal. 55 Gal. 275 Gal.



TRANSPORT INFORMATION:

Proper Shipping Name -
Corrosive Liquids, N.O.S.,
(Contains Sodium Hydroxide)
DOT Hazard Class - 8 Packing Group - III
ID# - UN 1760

Inhalation: Remove affected person to fresh air; wash mouth & nasal passages with water repeatedly. If breathing difficulty persists, seek medical attention.

Skin: Remove contaminated clothing; wash affected area with soap and water; if irritation persists, seek medical attention. DO NOT attempt to neutralize with chemical agents. Launder contaminated clothing before reuse.

Eyes: Remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; get medical attention immediately.

Ingestion: Drink large quantities of water or milk; give diluted vinegar or lemon juice to conscious person; DO NOT induce vomiting; seek medical attention.

PowerKleen

Quality Chemicals • Superior Service

Power Kleen Corporation

To Reorder, Call: (813) 854-2648

FAX (813) 854-3133

In Case Of Chemical Emergency Contact

Chem-Tel 24 Hours (800) 255-3924

www.PowerKleen.com