Printing date 10/30/2014 Reviewed on 01/10/2014

1 Identification

· Product identifier

· Trade name: Finally

· Article number: 1200 PK

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Power Kleen Corporation 101 South Bayview Blvd. OLDSMAR, FL 34677

USA

· Information department: Product Safety Department

• Emergency telephone number: ChemTel Inc. (800) 255-3924 Intl. +01 (813) 248-0585



2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:

2-aminoethanol

disodium metasilicate

· Hazard statements

Causes severe skin burns and eye damage.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Do not breathe dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/30/2014 Reviewed on 01/10/2014

Trade name: Finally

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 4Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
141-43-5	2-aminoethanol	2.5-10%	
	disodium metasilicate	2.5-10%	
	sodium hydroxide	≤ 2.5%	
	2-butoxyethanol	<i>≤</i> 2.5%	
	Disodium cocoamphodipropionate	≤ 2.5%	
	propan-2-ol	≤ 2.5%	
67-56-1	methanol	≤ 2.5%	

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. *In case of unconsciousness place patient stably in side position for transportation.*

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact:

Remove contact lenses if able to do so.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

A person vomiting while lying on their back should be turned onto their side.

Do not induce vomiting; immediately call for medical help.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

· Most important symptoms and effects, both acute and delayed Cramp

(Contd. on page 3)

Printing date 10/30/2014 Reviewed on 01/10/2014

Trade name: Finally

(Contd. of page 2)

Nausea

Headache

Dizziness

Gastric or intestinal disorders

- · Danger Danger of gastric perforation.
- · Indication of any immediate medical attention and special treatment needed

Medical supervision for at least 48 hours.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

 $We ar \ protective \ equipment. \ Keep \ unprotected \ persons \ away.$

- $\cdot \textbf{\textit{Environmental precautions:}} \ \textit{No special measures required.}$
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Unsuitable material for receptacle: glass or ceramic.

Unsuitable material for receptacle: aluminium.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Store under lock and key and out of the reach of children.

Keep receptacle tightly sealed.

· Specific end use(s) No further relevant information available.

TICA.

Printing date 10/30/2014 Reviewed on 01/10/2014

Trade name: Finally

(Contd. of page 3)

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit ve	alues that require	monitoring at th	he workplace:
----------------------------	--------------------	------------------	---------------

141-43-5 2-aminoethanol

- PEL Long-term value: 6 mg/m³, 3 ppm
- REL Short-term value: 15 mg/m³, 6 ppm Long-term value: 8 mg/m³, 3 ppm
- TLV Short-term value: 15 mg/m³, 6 ppm Long-term value: 7.5 mg/m³, 3 ppm

1310-73-2 sodium hydroxide

- PEL Long-term value: 2 mg/m³
- REL Ceiling limit value: 2 mg/m³
- TLV Ceiling limit value: 2 mg/m³

111-76-2 2-butoxyethanol

- PEL Long-term value: 240 mg/m³, 50 ppm
 - Skin
- REL Long-term value: 24 mg/m³, 5 ppm
 - Skin
- TLV Long-term value: 97 mg/m³, 20 ppm BEI

67-63-0 propan-2-ol

- PEL Long-term value: 980 mg/m³, 400 ppm
- REL Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm
- TLV Short-term value: 984 mg/m³, 400 ppm
 - Long-term value: 492 mg/m³, 200 ppm BEI

DLI

67-56-1 methanol

- PEL Long-term value: 260 mg/m³, 200 ppm
- REL Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm

Skin

TLV Short-term value: 328 mg/m³, 250 ppm

Long-term value: 262 mg/m³, 200 ppm

Skin; BEI

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Butoxyacetic acid with hydrolysis

(Contd. on page 5)

Printing date 10/30/2014 Reviewed on 01/10/2014

Trade name: Finally

(Contd. of page 4)

67-63-0 propan-2-ol

BEI 40 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

67-56-1 methanol

BEI 15 mg/L

Medium: urine Time: end of shift

Parameter: Methanol (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Neoprene gloves

PVC or PE gloves

Fluorocarbon rubber (Viton)

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Not suitable are gloves made of the following materials:

Strong gloves

Leather gloves

· Eye protection:



Tightly sealed goggles

-USA

Printing date 10/30/2014 Reviewed on 01/10/2014

Trade name: Finally

(Contd. of page 5)

	(Contd. or	pa
Physical and chemical proper	rties	
Information on basic physical and	chemical properties	
· General Information	• •	
Appearance:		
Form:	Liquid	
Color:	Blue	
· Odor:	Characteristic	
· Odour threshold:	Not determined.	
pH-value at 20 °C (68 °F):	13	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	385 °C (725 °F)	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure:	Not determined.	
Density at 20 °C (68 °F):	1.025 g/cm³ (8.554 lbs/gal)	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wat	er): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	11.9 %	
Water:	79.2 %	
VOC content:	20.8 %	
	122.2 g/l / 1.02 lb/gl	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 7)

Printing date 10/30/2014 Reviewed on 01/10/2014

Trade name: Finally

(Contd. of page 6)

· Possibility of hazardous reactions

Reacts with strong oxidizing agents.

Reacts with strong acids.

- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Sodium Oxides Nitrogen oxides

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC5	LD/LC50 values that are relevant for classification:			
141-43	5 2-am	inoethanol		
Oral	LD50	2050 mg/kg (rat)		
Dermal	LD50	1000 mg/kg (rabbit)		
1310-73	1310-73-2 sodium hydroxide			
Oral	LD50	2000 mg/kg (rat)		

- · Primary irritant effect:
- · on the skin: Strong caustic effect on skin and mucous membranes.
- · on the eye: Strong caustic effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (In	nternational Agency for Research on Cancer)			
111-76-2	2 2-butoxyethanol	3		
67-63-0	propan-2-ol	3		
· NTP (Na	· NTP (National Toxicology Program)			
None of t	the ingredients is listed.			
· OSHA-C	· OSHA-Ca (Occupational Safety & Health Administration)			
None of t	the ingredients is listed.			

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 8)

Printing date 10/30/2014 Reviewed on 01/10/2014

Trade name: Finally

(Contd. of page 7)

- · Additional ecological information:
- · General notes:

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, IMDG, IATA	UN1760
UN proper shipping name DOT IMDG, IATA	Corrosive liquids, n.o.s. (Sodium hydroxide, Ethanolamine) CORROSIVE LIQUID, N.O.S. (SODIUM HYDROXID) ETHANOLAMINE)
Transport hazard class(es)	
DOT	
OORROSIVE 8	
Class	8 Corrosive substances
Label	8
IMDG, IATA	
Class	8 Corrosive substances
Label	8
Packing group DOT, IMDG, IATA	III
Environmental hazards:	
Marine pollutant:	No

Printing date 10/30/2014 Reviewed on 01/10/2014

Trade name: Finally

	(Contd. of page
Special precautions for user	
Danger code (Kemler):	80
EMS Number:	F- A , S - B
Segregation groups	Alkalis
Transport in bulk according to Annex II o	nf .
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (\widetilde{EQ})	Code: E1
• • • • • •	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN1760, Corrosive liquids, n.o.s. (Sodium hydroxide
-	Ethanolamine), 8, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

· Section 355	(extremely	hazardous	substances):	
---------------	------------	-----------	--------------	--

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

111-76-2 2-butoxyethanol

67-63-0 propan-2-ol

7758-29-4 pentasodium triphosphate

67-56-1 methanol

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicalsknown to cause reproductive toxicity for males.

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

67-56-1 methanol

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

111-76-2 2-butoxyethanol

NL

(Contd. on page 10)

Printing date 10/30/2014 Reviewed on 01/10/2014

Trade name: Finally

(Contd. of page 9)

· TLV (Thi	reshold Limit Value established by ACGIH)	
111-76-2	2-butoxyethanol	<i>A3</i>
67-63-0	propan-2-ol	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labeling:

2-aminoethanol

disodium metasilicate

· Hazard statements

Causes severe skin burns and eye damage.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Do not breathe dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing MSDS:** Environment protection department.
- · Date of preparation / last revision 10/30/2014 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Skin Corr. 1A: Skin corrosion/irritation, Hazard Category 1A