Printing date 11/04/2014 Reviewed on 01/10/2014

1 Identification

- · Product identifier
- · Trade name: Non Ammoniated Stripper
- · Article number: 1205 PK
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Power Kleen Corporation 101 South Bayview Blvd. OLDSMAR, FL 34677 USA



Chemical Solutions Since 1973

- · Information department: Product Safety Department
- Emergency telephone number: ChemTel Inc. (800) 255-3924 Intl. +01 (813) 248-0585

2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.



Eye Irrit. 2A H319 Causes serious eye irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:

disodium metasilicate

· Hazard statements

Causes severe skin burns and eye damage.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Do not breathe dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet acc. to OSHA HCS

Printing date 11/04/2014 Reviewed on 01/10/2014

Trade name: Non Ammoniated Stripper

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 4 Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
111-76-2	2-butoxyethanol	2.5-10%
6834-92-0	disodium metasilicate	≤ 2.5%
66455-15-0	C10-12 6 Mole Linear Alcohol Ethoxylate	≤ 2.5%
1310-58-3	potassium hydroxide	≤ 2.5%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Remove contact lenses if able to do so.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

· Most important symptoms and effects, both acute and delayed

Nausea

Cramp

Dizziness

Headache

· Danger Danger of gastric perforation.

(Contd. on page 3)

Printing date 11/04/2014 Reviewed on 01/10/2014

Trade name: Non Ammoniated Stripper

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed Medical supervision for at least 48 hours.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment:

Wear fully protective suit.

Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Unsuitable material for receptacle: aluminium.

Unsuitable material for receptacle: glass or ceramic.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

Printing date 11/04/2014 Reviewed on 01/10/2014

Trade name: Non Ammoniated Stripper

(Contd. of page 3)

· Control parameters

· Components with limit values that require monitoring at the workplace:		
111-76-2 2-butoxyethanol		
PEL	Long-term value: 240 mg/m³, 50 ppm	
	Skin	

REL Long-term value: 24 mg/m³, 5 ppm Skin

TLV Long-term value: 97 mg/m³, 20 ppm BEI

1310-58-3 potassium hydroxide

REL Ceiling limit value: 2 mg/m³
TLV Ceiling limit value: 2 mg/m³

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine Medium: urine Time: end of shift

Parameter: Butoxyacetic acid with hydrolysis

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Neoprene gloves

Nitrile rubber, NBR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)


(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 11/04/2014 Reviewed on 01/10/2014

Trade name: Non Ammoniated Stripper

· Eye protection:



· Body protection: Alkaline resistant protective clothing

Physical and chemical proper	rties	
· Information on basic physical and	chemical properties	
· Information on basic physical and · General Information	chemical properties	
· Appearance:		
Form:	Liquid	
Color:	Blue	
· Odor:	Characteristic	
· Odour threshold:	Not determined.	
· pH-value at 20 °C (68 °F):	13.2	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:		
Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure:	Not determined.	
· Density at 20 °C (68 °F):	1.05 g/cm³ (8.762 lbs/gal)	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octanol/wat	ter): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	2.7 %	
Water:	91.4~%	

(Contd. on page 6)

Printing date 11/04/2014 Reviewed on 01/10/2014

Trade name: Non Ammoniated Stripper

	(Contd. of page 5)
VOC content:	2.7 % 33.2 g/l / 0.28 lb/gl
Solids content: Other information	5.9 % No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Reacts with strong acids and oxidizing agents.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:

Hydrocarbons

Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

1310-58-3 potassium hydroxide

Oral LD50 273 mg/kg (rat)

- · Primary irritant effect:
- \cdot on the skin: Strong caustic effect on skin and mucous membranes.
- · on the eye: Strong caustic effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· Carcinogenic categories	
· IARC (International Agency for Research on Cancer)	
111-76-2 2-butoxyethanol	3
· NTP (National Toxicology Program)	
None of the ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	

12 Ecological information

None of the ingredients is listed.

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.

(Contd. on page 7)

Printing date 11/04/2014 Reviewed on 01/10/2014

Trade name: Non Ammoniated Stripper

(Contd. of page 6)

- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

-	1 4 7	A CONTRACTOR OF THE CONTRACTOR		C	, •
		TOTAC	nort ini	OFWIN	701
			port ini	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	*****

•	UN-	Number	
---	-----	--------	--

· **DOT**, **IMDG**, **IATA** UN1719

· UN proper shipping name

· DOT Caustic alkali liquids, n.o.s. (Potassium hydroxide)

· IMDG, IATA CAUSTIC ALKALI LIQUID, N.O.S. (POTASSIUM HYDROXIDE)

· Transport hazard class(es)

 $\cdot DOT$



· Class 8 Corrosive substances

· Label

· IMDG, IATA



· Class 8 Corrosive substances

· Label 8

(Contd. on page 8)

Printing date 11/04/2014 Reviewed on 01/10/2014

Trade name: Non Ammoniated Stripper

	(Contd. of pag
· Packing group	
· DOT, IMDG, IATA	III
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	
Danger code (Kemler):	80
EMS Number:	F- A , S - B
Segregation groups	Alkalis
Transport in bulk according to Annex II of	•
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
· IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
· · · · · · · · · · · · · · · · · · ·	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN ''Model Regulation'':	UN1719, Caustic alkali liquids, n.o.s. (Potassium hydroxide), 8, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara			
· Section 355	· Section 355 (extremely hazardous substances):		
7601-54-9 t	risodium orthophosphate		
· Section 313	(Specific toxic chemical listings):		
111-76-2 2	2-butoxyethanol		
7758-29-4 p	pentasodium triphosphate		
7601-54-9 t	risodium orthophosphate		
· TSCA (Toxio	· TSCA (Toxic Substances Control Act):		
111-76-2	2-butoxyethanol		
6834-92-0	disodium metasilicate		
66455-15-0	C10-12 6 Mole Linear Alcohol Ethoxylate		
1310-58-3	potassium hydroxide		
7758-29-4	pentasodium triphosphate		
7601-54-9	trisodium orthophosphate		
64-02-8	tetrasodium ethylenediaminetetraacetate		
7732-18-5	water, distilled, conductivity or of similar purity		

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

(Contd. on page 9)

Printing date 11/04/2014 Reviewed on 01/10/2014

Trade name: Non Ammoniated Stripper

(Contd. of page 8)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicalsknown to cause reproductive toxicity for males.

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

111-76-2 2-butoxyethanol

NL

· TLV (Threshold Limit Value established by ACGIH)

111-76-2 2-butoxyethanol

A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:

disodium metasilicate

· Hazard statements

Causes severe skin burns and eye damage.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Do not breathe dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Environment protection department.
- · Date of preparation / last revision 11/04/2014 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

 $DOT: \ US \ Department \ of \ Transportation$

(Contd. on page 10)

Printing date 11/04/2014 Reviewed on 01/10/2014

Trade name: Non Ammoniated Stripper

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Skin Corr. 1A: Skin corrosion/irritation, Hazard Category 1A

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

(Contd. of page 9)