Printing date 05/30/2014

Reviewed on 05/29/2014

Printing date 05/30/2014	Reviewed on 05/29/2014
1 Identification	
· Product identifier	
· Trade name: <u>Wax Remover</u>	Jamson Labs
• Article number: 0122 JL • Application of the substance / the mixture Wax Remover	Quality Chemicals Since 1973
• Details of the supplier of the safety data sheet • Manufacturer/Supplier: Jamson Laboratories, Inc. 101 South Bayview Blvd. Oldsmar, FL 34677 USA	
• Information department: Product Safety Department • Emergency telephone number: ChemTel Inc. (800) 255-3924 Intl	+01 (813) 248-0585
2 Hazard(s) identification	
· Classification of the substance or mixture	
GHS02 Flame	
Flam. Liq. 2 H225 Highly flammable liquid and vapor.	
GHS08 Health hazard	
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.	
GHS07	
Skin Irrit. 2 H315 Causes skin irritation.	
• Label elements • GHS label elements The product is classified and labeled accordin • Hazard pictograms	g to the Globally Harmonized System (GHS).
GHS02 GHS07 GHS08	
· Signal word Danger	
 Hazard-determining components of labeling: Solvent naphtha (petroleum), light aliph. Hazard statements Highly flammable liquid and vapor. Causes skin irritation. May be fatal if swallowed and enters airways. 	

May be fatal if swallowed and enters airways.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

Printing date 05/30/2014

Reviewed on 05/29/2014

Trade name: Wax Remover

	(Contd. of page 1)
Keep out of reach of children.	
Read label before use.	
Keep away from heat/sparks/open flames/hot surfaces. No smoking.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.	
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with wa	iter/shower.
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulation.	<i>s</i> .
· Classification system:	
· NFPA ratings (scale 0 - 4)	
$\begin{array}{c} \textbf{Health} = 2\\ \textbf{Fire} = 3\\ \textbf{Reactivity} = 0 \end{array}$	
· HMIS-ratings (scale 0 - 4)	
HEALTH2Health = 2FIRE3Fire = 3REACTIVITY0Reactivity = 0	
· Other hazards	
· Results of PBT and vPvB assessment	
• PBT: Not applicable.	
· vPvB: Not applicable.	

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
	Solvent naphtha (petroleum), light aliph.	50-100%
1330-20-7	xylene (mix)	10-25%
111-76-2	2-butoxyethanol	2.5-10%
	propan-2-ol	2.5-10%
	Stoddard solvent	2.5-10%
	1,2,4-trimethylbenzene	<i>≤</i> 2.5%
108-67-8	mesitylene	<i>≤</i> 2.5%

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 3)

Printing date 05/30/2014

Reviewed on 05/29/2014

Trade name: Wax Remover

	(Contd. of page 2)
Remove contact lenses if able to do so.	
· After swallowing:	
Rinse out mouth and then drink plenty of water.	
Do not induce vomiting; immediately call for medical help.	
A person vomiting while lying on their back should be turned onto their side.	
· Information for doctor:	
· Most important symptoms and effects, both acute and delayed	
Nausea	
Gastric or intestinal disorders	
Cramp	
Dizziness	
Headache	
· Danger	
Danger of disturbed cardiac rhythm.	
Danger of pneumonia.	
Danger of pulmonary edema.	
· Indication of any immediate medical attention and special treatment needed	
In cases of irritation to the lungs, initial treatment with Dexamethason metered aerosol.	
Later observation for pneumonia and pulmonary edema.	
If swallowed or in case of vomiting, danger of entering the lungs.	

5 Fire-fighting measures

· Extinguishing media

- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture Carbon monoxide (CO)
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures	
Wear protective equipment. Keep unprotected persons away.	
• Environmental precautions:	
Do not allow product to reach sewage system or any water course.	
Inform respective authorities in case of seepage into water course or sewage system.	
Do not allow to enter sewers/ surface or ground water.	
• Methods and material for containment and cleaning up:	
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Dispose contaminated material as waste according to item 13.	
Ensure adequate ventilation.	
Do not flush with water or aqueous cleansing agents	
· Reference to other sections	
See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	

(Contd. on page 4)

(Contd. of page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 05/30/2014

Reviewed on 05/29/2014

Trade name: Wax Remover

7 Handling and storage

· Handling:

- *Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.*
- Information about protection against explosions and fires: Do not spray on a naked flame or any incandescent material. Flammable gas-air mixtures may be formed in empty receptacles. Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Store away from oxidizing agents. Store away from foodstuffs.
- Further information about storage conditions: Keep receptacle tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

Components with limit values that require monitoring at the workplace 1330-20-7 xylene (mix)	
PEL Long-term value: 435 mg/m ³ , 100 ppm	
REL Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm	
TLV Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI	
111-76-2 2-butoxyethanol	
PEL Long-term value: 240 mg/m ³ , 50 ppm Skin	
REL Long-term value: 24 mg/m³, 5 ppm Skin	
TLV Long-term value: 97 mg/m³, 20 ppm BEI	
67-63-0 propan-2-ol	
PEL Long-term value: 980 mg/m ³ , 400 ppm	
REL Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm	
TLV Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm BEI	
	(Contd. on page 3

Printing date 05/30/2014

Reviewed on 05/29/2014

Trade name: Wax Remover

114	
	(Contd. of page 4)
	8052-41-3 Stoddard solvent
	PEL Long-term value: 2900 mg/m ³ , 500 ppm
	REL Long-term value: 350 ppm
	Ceiling limit value: 1800* mg/m ³
	*15-min
	TLV Long-term value: 525 mg/m ³ , 100 ppm
•	Ingredients with biological limit values:
	1330-20-7 xylene (mix)
	BEI 1.5 g/g creatinine
	Medium: urine
	Time: end of shift
	Parameter: Methylhippuric acids
	111-76-2 2-butoxyethanol
	BEI 200 mg/g creatinine
	Medium: urine
	Time: end of shift
	Parameter: Butoxyacetic acid with hydrolysis
	67-63-0 propan-2-ol
	BEI 40 mg/L
	Medium: urine
	Time: end of shift at end of workweek
	Parameter: Acetone (background, nonspecific)
•.	Additional information: The lists that were valid during the creation were used as basis.
	Exposure controls
	Personal protective equipment:
	General protective and hygienic measures:
	Keep away from foodstuffs, beverages and feed.
	Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.
	Breathing equipment:
	In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use
	respiratory protective device that is independent of circulating air.
	Protection of hands:
	Protective cloves
	Protective gloves
	The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
	Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the
	chemical mixture.
	Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
	Material of gloves
	PVC or PE gloves Nitrile rubber, NBR
	Fluorocarbon rubber (Viton)
	The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and
	varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of
	the glove material can not be calculated in advance and has therefore to be checked prior to the application.
	(Contd. on page 6)
	- USA

(Contd. of page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 05/30/2014

Reviewed on 05/29/2014

Trade name: Wax Remover

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Not suitable are gloves made of the following materials:

Strong gloves Natural rubber, NR

Leather gloves

· Eye protection:

Tightly sealed goggles

· Body protection: Solvent resistant protective clothing

Information on basic physical and a	chemical properties
General Information	
Appearance: Form:	Liquid
Form. Color:	Amber colored
Odor:	Hydrocarbon
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	60 °C (140 °F)
Flash point:	12 °C (54 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	240 °C (464 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.0 Vol %
Vapor pressure at 20 °C (68 °F):	6.7 hPa (5 mm Hg)
Density at 20 °C (68 °F):	0.74 g/cm ³ (6.175 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.

USA

Printing date 05/30/2014

Reviewed on 05/29/2014

Trade name: Wax Remover

		(Contd. of page
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	95.2 %	
Water:	0.1 %	
VOC content:	95.3 %	
	704.5 g/l / 5.88 lb/gl	
• Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions

Flammable.

- Reacts with oxidizing agents.
- \cdot Conditions to avoid No further relevant information available.
- $\cdot \textit{Incompatible materials: } No further relevant information available.$
- · Hazardous decomposition products:
- Hydrocarbons
- Carbon monoxide and carbon dioxide

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

1330-20-7 xylene (mix)

Oral LD50 4300 mg/kg (rat) Dermal LD50 2000 mg/kg (rabbit)

· Primary irritant effect:

• on the skin:

Irritant to skin and mucous membranes. No irritant effect.

- on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:
- Irritant

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

· Carcinogenic categories

· IARC (Inte	ernational Agency for Research on Cancer)	
1330-20-7	xylene (mix)	3
111-76-2	2-butoxyethanol	3
67-63-0	propan-2-ol	3
	(Contd. on p	page 8)

USA

Printing date 05/30/2014

Reviewed on 05/29/2014

Trade name: Wax Remover

(Contd. of page 7)

· NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- \cdot Additional ecological information:
- · General notes:
- Water hazard class 2 (Self-assessment): hazardous for water
- $Do \ not \ allow \ product \ to \ reach \ ground \ water, \ water \ course \ or \ sewage \ system.$

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	Not applicable UN1993
DOT, IMDG, IATA	011995
UN proper shipping name DOT	Elammable liquide a o s. (Solvent nanktha (netroloum) light aligh
<i>b</i> 01	Flammable liquids, n.o.s. (Solvent naphtha (petroleum), light aliph Isopropanol (Isopropyl alcohol))
IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (Solvent naphtha (petroleum), ligh
	aliph., ISOPROPANOL (ISOPROPYL ALCOHOL))
Transport hazard class(es)	
DOT	
3	
Combustible Liquid	
Class	3 Flammable liquids.

Printing date 05/30/2014

Reviewed on 05/29/2014

Trade name: Wax Remover

	(Contd. of page
· Label	3
· IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· Packing group	
· DOT, IMDG, IATA	II
Environmental hazards:	
Marine pollutant:	No
· Special precautions for user	
· Danger code (Kemler):	33
· EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>
• Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	UN1993, Flammable liquids, n.o.s. (Solvent naphtha (petroleum light aliph., Isopropanol (Isopropyl alcohol)), 3, II

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

Section 355 (extremely	hazardous substances):
------------------------	------------------------

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

1330-20-7 xylene (mix)

67-63-0 propan-2-ol

95-63-6 1,2,4-trimethylbenzene

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

 \cdot Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicalsknown to cause reproductive toxicity for males.

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 10)

USA -

Printing date 05/30/2014

Reviewed on 05/29/2014

Trade name: Wax Remover

(Contd. of page 9)

1

NL

A4

A3

A4

• (Carcinog	enic	categories
-----	----------	------	------------

· EPA (Environmental Protection Agency)

1330-20-7 xylene (mix)

111-76-2 2-butoxyethanol

· TLV (Threshold Limit Value established by ACGIH)

1330-20-7 xylene (mix)

111-76-2 2-butoxyethanol

67-63-0 propan-2-ol

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

Substance is listed as a suspected carcinogen.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

- · Hazard-determining components of labeling:
- Solvent naphtha (petroleum), light aliph.
- · Hazard statements

Highly flammable liquid and vapor. Causes skin irritation.

May be fatal if swallowed and enters airways.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children. Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Environment protection department.
- Date of preparation / last revision 5/29/2014
- Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation

(Contd. on page 11)

USA

Printing date 05/30/2014

Reviewed on 05/29/2014

Trade name: Wax Remover

IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent (Contd. of page 10)

USA -