

# Floating Degreaser

**PRODUCT #:** PK-1636

## CHARACTERISTICS:

Appearance: Clear liquid  
 Odor: Citrus  
 pH: 6.00  
 Specific Gravity: 0.800  
 Weight: 6.67  
 Viscosity: Water Like  
 Flash Point: N/A  
 Dilution: Ready To Use

## ADVANTAGES:

This is a professional grade, super-concentrate that frees hung up or stuck floating digestion covers by merely applying around outer perimeter of cover and immediately wetting with ordinary garden hose.

## DIRECTIONS:

**AS A PREVENTATIVE MAINTENANCE MEASURE:** Drip product in the influent at the rate of ¼ to 1-1/2 ppm. (45 drops per minute equals one gallon in 24 hours). A simple water gate valve will maintain drip once set, as low as one pint per day. Drip directly into wet wells and lift stations. Add directly to sewer lines and force mains to remove grease build up.

**ELIMINATES GREASE OR SCUM CAKES IN DIGESTER:** Introduce through top digester in any port or inspection holes; 20 to 25 gallons is a good average guideline to follow. After introducing add 500 to 2000 gallons of water, continue to wet down top of grease cake daily. After treating digester, add 1 to 2 gallons daily in sludge compartments. In doing this you are working on the grease cake from top to bottom. After adding through sludge compartment continue circulation as usual.

## PRECAUTIONS:

**Inhalation:** None Expected. Remove affected person to fresh air; if symptoms persist seek medical attention.

**Skin:** None Expected. Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

**Eyes:** Check for and remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

**Ingestion:** Give two glasses of water for dilution; DO NOT induce vomiting; never give anything by mouth to an unconscious person; seek medical attention.

## TRANSPORT INFO:

Proper Shipping Name - Not Regulated for Transport by Truck  
 DOT Hazard Class - Not Regulated  
 Packing Group - Not Regulated  
 ID# - Not Regulated

**GUARANTEE:** Jamson Labs' / Power Kleen's manufacturing and laboratory controls ensure uniform quality throughout our product line. All Jamson Labs / Power Kleen manufactured products are guaranteed for 1 year when used as directed.



## AVAILABLE IN:

Gal. Jug, 5 Gal. Bucket, 55 Gal. Drum,  
 275 Gal. Tote, 300 Gal. Leg Tank or delivered via Tanker Truck

