

# Vat Dip

 - Heavy Duty Cleaner For Vat Dip Systems**PRODUCT #:** PK-1800**CHARACTERISTICS:**

Appearance: White  
 Odor: Odorless  
 pH: 13.00  
 Specific Gravity: N/A  
 Weight  
 Viscosity: Powder  
 Flash Point: N/A  
 Dilution: 1 LB Per Gal

**ADVANTAGES:**

Vat Dip is an industrial-strength heavy-duty cleaner for vat dip systems for steel engine blocks and fabricated steel parts. It efficiently removes paint, grease and carbon.

**DIRECTIONS:**

Charge the soak tank with one (1) pound of cleaner to one (1) gallon of water. Raise temperature to 175° F to 185° F. Although the chemical easily dissolves, the solution should be stirred with a paddle to prevent caking at the bottom of the tank. Load the tank with parts to be cleaned and soak for 1 to 2 hours at 175° F - 185° F. Soaking time will depend on soil and paint accumulation. Remove cleaned parts and rinse away soil by water. Most of the soil that is removed will drop to the bottom of the tank where it can be drained out. Recharge with chemical and water if needed for re-use.

**PRECAUTIONS:**

**Inhalation:** Remove affected person to fresh air; wash mouth and nasal passages with water repeatedly; if breathing difficulties persist seek medical attention.

**Skin:** Remove contaminated clothing; wash affected area with soap and water; DO NOT attempt to neutralize with chemical agents; if irritation persists, seek medical attention. Launder contaminated clothing before reuse.

**Eyes:** Check for and remove any contact lenses. Immediately flush eyes with clear running water for 15 minutes while holding eyelids open. Seek medical attention immediately.

**Ingestion:** Drink two glasses of water or milk; give diluted vinegar or lemon juice to conscious person; DO NOT induce vomiting; seek medical attention immediately.

**TRANSPORT INFO:**

Proper Shipping Name - Corrosive Solids, N.O.S.,  
 (Contains Sodium Metasilicate)  
 DOT Hazard Class - 8  
 Packing Group - III  
 ID# - UN 1759

**AVAILABLE IN:**

Gal. Jug, 5 Gal. Bucket or 55 Gal. Drum,



**GUARANTEE:** Jamson Labs' / Power Kleen's manufacturing and laboratory controls ensure uniform quality throughout our product line. All Jamson Labs / Power Kleen manufactured products are guaranteed for 1 year when used as directed.