Printing date 02/04/2014 Reviewed on 01/29/2014

## 1 Identification

· Product identifier

· Trade name: Carpet Steam

· Article number: 1820 PK

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Power Kleen Corporation 101 South Bayview Blvd. OLDSMAR, FL 34677 USA



**Chemical Solutions Since 1973** 

- · Information department: Product Safety Department
- Emergency telephone number: ChemTel Inc. (800) 255-3924 Intl. +01 (813) 248-0585

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.



STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

disodium metasilicate

· Hazard statements

Causes severe skin burns and eye damage.

May cause respiratory irritation.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Do not breathe dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

Store locked up.

(Contd. on page 2)

Printing date 02/04/2014 Reviewed on 01/29/2014

Trade name: Carpet Steam

(Contd. of page 1)

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:				
6834-92-0	disodium metasilicate	25-50%		
26447-10-9	Sodium Alkyl Napthalene Sulfonate	2.5-10%		
	Fragrance (Generic)	≤ 2.5%		

## 4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

*In case of unconsciousness place patient stably in side position for transportation.* 

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Remove contact lenses if able to do so.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

A person vomiting while lying on their back should be turned onto their side.

Do not induce vomiting; immediately call for medical help.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

Nausea

Coughing

Gastric or intestinal disorders

Cramp

(Contd. on page 3)

Printing date 02/04/2014 Reviewed on 01/29/2014

Trade name: Carpet Steam

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed Medical supervision for at least 48 hours.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Avoid formation of dust.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Do not store together with acids.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

Printing date 02/04/2014 Reviewed on 01/29/2014

Trade name: Carpet Steam

(Contd. of page 3)

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

#### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Neoprene gloves

PVC gloves

Nitrile rubber, NBR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Not suitable are gloves made of the following materials: Leather gloves
- · Eye protection:

Safety glasses



Tightly sealed goggles

· Body protection: Alkaline resistant protective clothing

## 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Powder
Color: White
Odor: Lemon

(Contd. on page 5)

Printing date 02/04/2014 Reviewed on 01/29/2014

Trade name: Carpet Steam

	(Contd. of p	pag			
Odour threshold:	Not determined.				
pH-value:	12.9				
Change in condition					
Melting point/Melting range:	Undetermined.				
Boiling point/Boiling range:	Undetermined.				
Flash point:	Not applicable.				
Flammability (solid, gaseous):	Not applicable.				
Ignition temperature:					
Decomposition temperature:	Not determined.				
Auto igniting:	Product is not selfigniting.				
Danger of explosion:	Product does not present an explosion hazard.				
Explosion limits:					
Lower:	Not determined.				
Upper:	Not determined.				
Vapor pressure:	Not determined.				
Density:	Not determined.				
Relative density	Not determined.				
Vapour density	Not determined.				
Evaporation rate	Not determined.				
Solubility in / Miscibility with					
Water:	Fully miscible.				
Partition coefficient (n-octanol/wat	ter): Not determined.				
Viscosity:					
Dynamic:	Not determined.				
Kinematic:	Not determined.				
Solvent content:					
Organic solvents:	0.0 %				
Water:	0.3 %				
Solids content:	99.8 %				
ther information No further relevant information available.					

## 10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Reacts with strong acids.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:

Sulfur oxides (SOx)

Phosphorus oxides (e.g. P2O5)

Sodium Oxides

(Contd. on page 6)

Printing date 02/04/2014 Reviewed on 01/29/2014

Trade name: Carpet Steam

Carbon monoxide and carbon dioxide

(Contd. of page 5)

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

#### 6834-92-0 disodium metasilicate

Oral LD50 1280 mg/kg (rat)

- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye: Strong caustic effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

1

· NTP (National Toxicology Program)

None of the ingredients is listed.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Printing date 02/04/2014 Reviewed on 01/29/2014

Trade name: Carpet Steam

(Contd. of page 6)

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

## 14 Transport information

			_	_
	TII	<i>J</i> 7	Viin	ıher
•		v - /	V 14.11	unei

· IMDG, IATA

· DOT, IMDG, IATA

UN1760

· UN proper shipping name

 $\cdot DOT$ 

Corrosive liquids, n.o.s. (Disodium trioxosilicate)

CORROSIVE LIQUID, N.O.S. (DISODIUM TRIOXOSILICATE)

- · Transport hazard class(es)
- $\cdot DOT$



· Class · Label 8 Corrosive substances.

O

· IMDG, IATA



· Class

8 Corrosive substances.

· Label

8

- · Packing group
- · DOT, IMDG, IATA

III

- *B*01, 1,1120, 1,1171
- Environmental hazards:Marine pollutant:

No

· Special precautions for user

Warning: Corrosive substances

· Danger code (Kemler):

80

· EMS Number:

F-A,S-B

· Segregation groups

Alkalis

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code

Not applicable.

· UN "Model Regulation":

UN1760, Corrosive liquids, n.o.s. (Disodium trioxosilicate), 8, III

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 8)

Printing date 02/04/2014 Reviewed on 01/29/2014

Trade name: Carpet Steam

(Contd. of page 7)

· Section	313	(Specific	toxic	chemical	listings):
Section	010	(Specific	wall	citciittat	usungs,.

7758-29-4 pentasodium triphosphate

### · TSCA (Toxic Substances Control Act):

7758-29-4 pentasodium triphosphate

6834-92-0 disodium metasilicate

26447-10-9 Sodium Alkyl Napthalene Sulfonate

7732-18-5 water, distilled, conductivity or of similar purity

#### · Proposition 65

#### · Chemicals known to cause cancer:

91-20-3 naphthalene

#### · Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

#### · Chemicalsknown to cause reproductive toxicity for males.

None of the ingredients is listed.

#### · Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

### · EPA (Environmental Protection Agency)

None of the ingredients is listed.

### · TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

## · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05

GHS07

### · Signal word Danger

#### · Hazard-determining components of labeling:

disodium metasilicate

#### · Hazard statements

Causes severe skin burns and eye damage.

May cause respiratory irritation.

#### · Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Do not breathe dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 9)

Printing date 02/04/2014 Reviewed on 01/29/2014

Trade name: Carpet Steam

(Contd. of page 8)

Immediately call a POISON CENTER or doctor/physician.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Environment protection department.
- · Date of preparation / last revision 01/29/2014
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

USA