

# Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2014

Reviewed on 01/30/2014

## 1 Identification

- **Product identifier**
- **Trade name:** P.O.G. (Paint , Oil and Grease
- **Article number:** 2200 PK
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Power Kleen Corporation  
101 South Bayview Blvd.  
OLDSMAR, FL 34677  
USA
- **Information department:** Product Safety Department
- **Emergency telephone number:** ChemTel Inc. (800) 255-3924 Intl. +01 (813) 248-0585



## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.  
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.  
Eye Irrit. 2A H319 Causes serious eye irritation.

H227 Combustible liquid.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07



GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**  
dichloromethane  
Stoddard solvent
- **Hazard statements**  
Combustible liquid.  
Causes skin irritation.  
Causes serious eye irritation.  
Suspected of causing cancer.  
May be fatal if swallowed and enters airways.

(Contd. on page 2)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2014

Reviewed on 01/30/2014

Trade name: P.O.G. (Paint , Oil and Grease)

(Contd. of page 1)

- **Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 2

Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = \*2

Fire = 2

Reactivity = 0

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

75-09-2	dichloromethane	25-50%
8052-41-3	Stoddard solvent	25-50%
66455-15-0	C10-12 6 Mole Linear Alcohol Ethoxylate	10-25%
95-63-6	1,2,4-trimethylbenzene	≤ 2.5%
108-67-8	mesitylene	≤ 2.5%

### 4 First-aid measures

- **Description of first aid measures**

- **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Generally the product does not irritate the skin.

- **After eye contact:**

Remove contact lenses if able to do so.

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2014

Reviewed on 01/30/2014

**Trade name: P.O.G. (Paint , Oil and Grease**

(Contd. of page 2)

*Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.*

· **After swallowing:**

*Do not induce vomiting; immediately call for medical help.*

*A person vomiting while lying on their back should be turned onto their side.*

*Immediately call a doctor.*

· **Most important symptoms and effects, both acute and delayed**

*Breathing difficulty*

*Headache*

*Dizziness*

*Coughing*

*Nausea*

*Unconsciousness*

*Gastric or intestinal disorders*

· **Indication of any immediate medical attention and special treatment needed**

*If swallowed or in case of vomiting, danger of entering the lungs.*

*Medical supervision for at least 48 hours.*

## 5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

*CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.*

· **Special hazards arising from the substance or mixture** Phosgene gas

· **Advice for firefighters**

· **Protective equipment:** Mouth respiratory protective device.

## 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

*Use respiratory protective device against the effects of fumes/dust/aerosol.*

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).*

*Dispose contaminated material as waste according to item 13.*

*Ensure adequate ventilation.*

· **Reference to other sections**

*See Section 7 for information on safe handling.*

*See Section 8 for information on personal protection equipment.*

*See Section 13 for disposal information.*

## 7 Handling and storage

· **Precautions for safe handling**

*Ensure good ventilation/exhaustion at the workplace.*

*Prevent formation of aerosols.*

· **Information about protection against explosions and fires:** Protect from heat.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** No special requirements.

· **Information about storage in one common storage facility:**

*Store away from reducing agents.*

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2014

Reviewed on 01/30/2014

**Trade name: P.O.G. (Paint , Oil and Grease**

(Contd. of page 3)

Store away from oxidizing agents.

Store away from foodstuffs.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

· **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

**75-09-2 dichloromethane**

PEL Short-term value: 125 ppm

Long-term value: 25 ppm

see 29 CFR 1910.1052

REL See Pocket Guide App. A

TLV Long-term value: 174 mg/m<sup>3</sup>, 50 ppm

BEI

**8052-41-3 Stoddard solvent**

PEL Long-term value: 2900 mg/m<sup>3</sup>, 500 ppm

REL Long-term value: 350 ppm

Ceiling limit value: 1800\* mg/m<sup>3</sup>

\*15-min

TLV Long-term value: 525 mg/m<sup>3</sup>, 100 ppm

· **Ingredients with biological limit values:**

**75-09-2 dichloromethane**

BEI 0.3 mg/L

Medium: urine

Time: end of shift

Parameter: Dichloromethane (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

(Contd. on page 5)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2014

Reviewed on 01/30/2014

**Trade name: P.O.G. (Paint , Oil and Grease**

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Neoprene gloves

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Not suitable are gloves made of the following materials:** Leather gloves

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Solvent resistant protective clothing

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

<b>Form:</b>	Liquid
<b>Color:</b>	Colorless
<b>Odor:</b>	Petroleum-like
<b>Odour threshold:</b>	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	176 °C (349 °F)

· **Flash point:** 61 °C (142 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 230 °C (446 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Not determined.

· **Explosion limits:**

<b>Lower:</b>	1.1 Vol %
<b>Upper:</b>	22.0 Vol %

· **Vapor pressure at 20 °C (68 °F):** 453 hPa (340 mm Hg)

· **Density at 20 °C (68 °F):** 0.73 g/cm<sup>3</sup> (6.092 lbs/gal)

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

(Contd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2014

Reviewed on 01/30/2014

Trade name: P.O.G. (Paint , Oil and Grease)

(Contd. of page 5)

- |   |  |
|---|--|
| <b>· Solubility in / Miscibility with Water:</b>  | Not miscible or difficult to mix.          |
| <b>· Partition coefficient (n-octanol/water):</b> | Not determined.                            |
| <b>· Viscosity:</b>                               |  |
| <b>Dynamic:</b>                                   | Not determined.                            |
| <b>Kinematic:</b>                                 | Not determined.                            |
| <b>· Solvent content:</b>                         |  |
| <b>Organic solvents:</b>                          | 44.0 %                                     |
| <b>VOC content:</b>                               | 1.2 %                                      |
|   | 8.9 g/l / 0.07 lb/gl                       |
| <b>· Other information</b>                        | No further relevant information available. |

## 10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions**
  - Reacts with reducing agents.
  - Reacts with strong oxidizing agents.
  - Flammable.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
  - Carbon monoxide and carbon dioxide
  - Hydrocarbons
  - Phosgene

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

### 75-09-2 dichloromethane

Oral	LD50	1600 mg/kg (rat)
Inhalative	LC50/4 h	88 mg/l (rat)

- **Primary irritant effect:**
  - on the skin:** No irritant effect.
  - on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
  - The product shows the following dangers according to internally approved calculation methods for preparations:
  - Harmful
  - Irritant
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

75-09-2 dichloromethane

2B

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2014

Reviewed on 01/30/2014

**Trade name: P.O.G. (Paint , Oil and Grease**

(Contd. of page 6)

1330-20-7 xylene (mix)

3

· **NTP (National Toxicology Program)**

75-09-2 dichloromethane

R

· **OSHA-Ca (Occupational Safety & Health Administration)**

75-09-2 dichloromethane

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
 Water hazard class 2 (Self-assessment): hazardous for water  
 Do not allow product to reach ground water, water course or sewage system.  
 Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>· <b>UN-Number</b></li> <li>· <b>DOT, IMDG, IATA</b></li> </ul>                                | UN2810   |
| <ul style="list-style-type: none"> <li>· <b>UN proper shipping name</b></li> <li>· <b>DOT</b></li> <li>· <b>IMDG, IATA</b></li> </ul> | Toxic, liquids, organic, n.o.s. (Dichloromethane)<br>TOXIC LIQUID, ORGANIC, N.O.S. (DICHLOROMETHANE) |
| <ul style="list-style-type: none"> <li>· <b>Transport hazard class(es)</b></li> <li>· <b>DOT</b></li> </ul>                           |  |
| <ul style="list-style-type: none"> <li>· <b>Class</b></li> </ul>  | 6.1 Toxic substances   |



(Contd. on page 8)

USA

# Safety Data Sheet


acc. to OSHA HCS

Printing date 11/04/2014

Reviewed on 01/30/2014

Trade name: P.O.G. (Paint , Oil and Grease)

(Contd. of page 7)

· <b>Label</b>	6.1
· <b>IMDG, IATA</b>	
	
· <b>Class</b>	6.1 Toxic substances
· <b>Label</b>	6.1
· <b>Packing group</b>	
· <b>DOT, IMDG, IATA</b>	III
· <b>Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b>	
· <b>Danger code (Kemler):</b>	60
· <b>EMS Number:</b>	F-A,S-A
· <b>Segregation groups</b>	Liquid halogenated hydrocarbons
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	
Not applicable.	
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Quantity limitations</b>	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN2810, Toxic, liquids, organic, n.o.s. (Dichloromethane), 6.1, III

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

75-09-2	dichloromethane
---------	-----------------

95-63-6	1,2,4-trimethylbenzene
---------	------------------------

1330-20-7	xylene (mix)
-----------	--------------

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

75-09-2	dichloromethane
---------	-----------------

(Contd. on page 9)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 11/04/2014

Reviewed on 01/30/2014

**Trade name: P.O.G. (Paint , Oil and Grease**

(Contd. of page 8)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males.**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

75-09-2	dichloromethane	L
1330-20-7	xylene (mix)	I

· **TLV (Threshold Limit Value established by ACGIH)**

75-09-2	dichloromethane	A3
1330-20-7	xylene (mix)	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

75-09-2	dichloromethane
---------	-----------------

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07    GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

dichloromethane

Stoddard solvent

· **Hazard statements**

Combustible liquid.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

May be fatal if swallowed and enters airways.

· **Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

USA

(Contd. on page 10)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 11/04/2014

Reviewed on 01/30/2014

**Trade name: P.O.G. (Paint , Oil and Grease**

(Contd. of page 9)

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Department issuing MSDS:** Environment protection department.

· **Date of preparation / last revision**

11/04/2014 / -

01/30/2014

· **Abbreviations and acronyms:**

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*DOT: US Department of Transportation*

*IATA: International Air Transport Association*

*ACGIH: American Conference of Governmental Industrial Hygienists*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*NFPA: National Fire Protection Association (USA)*

*HMIS: Hazardous Materials Identification System (USA)*

*VOC: Volatile Organic Compounds (USA, EU)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*: Flammable liquids, Hazard Category 4*

*Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2*

*Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A*

*Carc. 2: Carcinogenicity, Hazard Category 2*

*Asp. Tox. 1: Aspiration hazard, Hazard Category 1*