Jamson Labs

Quality Chemicals Since 1973

Safety Data Sheet acc. to OSHA HCS

Printing date 10/14/2014 Reviewed on 12/19/2013

1 Identification

- · Product identifier
- · Trade name: Jamson Mineral Spirits
- · Article number: 0130JLM · CAS Number: Mixture
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Jamson Laboratories, Inc. 101 South Bayview Blvd. Oldsmar, FL 34677

USA

Tiger Blend Chemicals, LLC.

P.O. Box 53451 Shreveport, LA 71135

- · Information department: Product Safety Department
- · Emergency telephone number: ChemTel Inc. (800) 255-3924 Intl. +01 (813) 248-0585

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Stoddard solvent

· Hazard statements

Flammable liquid and vapour.

May be fatal if swallowed and enters airways.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

(Contd. on page 2)

Printing date 10/14/2014 Reviewed on 12/19/2013

Trade name: Jamson Mineral Spirits

(Contd. of page 1)

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1Fire = 2Reactivity = 0

· HMIS-ratings (scale 0 - 4)



1 Health = 1Fire = 2

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description

8052-41-3 Stoddard solvent

- · Identification number(s)
- · EC number: 232-489-3
- · Index number: 649-345-00-4
- · Chemical characterization: Mixtures
- · **Description**: Mixture of the substances listed below with nonhazardous additions.

· Dangerou	· Dangerous components:		
8052-41-3	Stoddard solvent	50-100%	
95-63-6	1,2,4-trimethylbenzene	2.5-10%	

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Generally the product does not irritate the skin.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

· Most important symptoms and effects, both acute and delayed

Nausea

Cramp

Gastric or intestinal disorders

Dizziness

(Contd. on page 3)

Printing date 10/14/2014 Reviewed on 12/19/2013

Trade name: Jamson Mineral Spirits

(Contd. of page 2)

Headache

- · Danger Danger of impaired breathing.
- · Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

· Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 4)

Printing date 10/14/2014 Reviewed on 12/19/2013

Trade name: Jamson Mineral Spirits

· Specific end use(s) No further relevant information available.

(Contd. of page 3)

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

8052-41-3 Stoddard solvent

PEL Long-term value: 2900 mg/m³, 500 ppm

REL Long-term value: 350 ppm

Ceiling limit value: 1800* mg/m³

*15-min

TLV Long-term value: 525 mg/m³, 100 ppm

95-63-6 1,2,4-trimethylbenzene

REL Long-term value: 125 mg/m³, 25 ppm TLV Long-term value: 123 mg/m³, 25 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Neoprene gloves

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Not suitable are gloves made of the following materials: Leather gloves
- · Eye protection:



Tightly sealed goggles

· **Body protection:** Solvent resistant protective clothing

Printing date 10/14/2014 Reviewed on 12/19/2013

Trade name: Jamson Mineral Spirits

(Contd. of page 4)

Physical and chemical propert	ties
· Information on basic physical and c · General Information	hemical properties
Appearance: Form:	Liquid
Color:	Clear
· Odor:	Petroleum-like
· Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	157 °C (315 °F)
· Flash point:	40 °C (104 °F)
Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	230 °C (446 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vap mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	6.0 Vol %
· Vapor pressure at 20 °C (68 °F):	4 hPa (3 mm Hg)
Density at 20 °C (68 °F):	0.77 g/cm³ (6.426 lbs/gal)
Relative density	Not determined.
· Vapour density at 20 °C (68 °F)	4.7 g/cm³ (39.222 lbs/gal)
Evaporation rate at 20 °C (68 °F)	0.20 (nBuAc=1)
Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	*
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	5.3 %
VOC content:	5.3 %
	40.7 g/l / 0.34 lb/gl
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 6)

Printing date 10/14/2014 Reviewed on 12/19/2013

Trade name: Jamson Mineral Spirits

(Contd. of page 5)

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

95-63-6 1,2,4-trimethylbenzene

Oral LD50 5000 mg/kg (rat)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

1330-20-7 xylene (mix)

3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Harmful to aquatic organisms

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

USA

Printing date 10/14/2014 Reviewed on 12/19/2013

Trade name: Jamson Mineral Spirits

(Contd. of page 6)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

Transport information	
UN-Number	
DOT	Not regulated
IMDG, IATA	UN1268
UN proper shipping name	Not were duted
DOT	Not regulated
MDG, IATA	PETROLEUM DISTILLATES, N.O.S.
Transport hazard class(es)	
DOT	Not applicable
MDG, IATA	
3	
Class	3 Flammable liquids
Label	3
Packing group	
DOT	Not applicable
MDG, IATA	III
· · · · · · · · · · · · · · · · · · ·	
Environmental hazards:	37
Marine pollutant:	No
Special precautions for user	
Danger code (Kemler):	30
EMS Number:	F-E, <u>S-E</u>
Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
Fransport/Additional information:	
DOT	Not regulated non-bulk <119 gal , Bulk UN1268 Class 3.
Quantity limitations	On cargo aircraft only: 220 L
	on cargo arciagi omy. 220 D
MDG	C.Y.
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml

Printing date 10/14/2014 Reviewed on 12/19/2013

Trade name: Jamson Mineral Spirits

(Contd. of page 7)

· UN "Model Regulation":

UN1268, Petroleum distillates, n.o.s., 3, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

95-63-6 1,2,4-trimethylbenzene

1330-20-7 xylene (mix)

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicalsknown to cause reproductive toxicity for males.

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

1330-20-7 xylene (mix)

I

· TLV (Threshold Limit Value established by ACGIH)

1330-20-7 xylene (mix)

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

- · Signal word Danger
- · Hazard-determining components of labeling:

Stoddard solvent

· Hazard statements

Flammable liquid and vapour.

May be fatal if swallowed and enters airways.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

(Contd. on page 9)

Printing date 10/14/2014 Reviewed on 12/19/2013

Trade name: Jamson Mineral Spirits

(Contd. of page 8)

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Environment protection department.
- · Contact: Product Safety Department
- · Date of preparation / last revision 10/14/2014 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

-USA