

Gone - Foam Control Concentrate**PRODUCT #:** PK-2500**CHARACTERISTICS:**

Appearance: White Liquid
 Odor: Characteristic
 pH: 7.00
 Specific Gravity: 1.000
 Weight: 8.34
 Viscosity: Water Like
 Flash Point: N/A
 Dilution: 1:128

ADVANTAGES:

This multi-purpose industrial-grade concentrated defoamer is now more stable and longer lasting. For general use in hot or cold systems — there's no need to shake or mix due to separation like other products.

DIRECTIONS:

CARPET STEAM EXTRACTORS: As a starting point add 1/2 to 1 ounce of defoamer to 10 gallons of waste solution tank capacity. Unusual jobs may require a second addition. **AUTOMATIC FLOOR SCRUBBERS:** For foaming problems in waste solution tanks add 1 to 2 ounces of defoamer per 10 gallons of water in solution tank.

PRECAUTIONS:

Inhalation: None Expected. Remove affected person to fresh air; if symptoms persist seek medical attention.

Skin: None Expected. Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

Eyes: Check for and remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

Ingestion: Give two glasses of water for dilution; DO NOT induce vomiting; never give anything by mouth to an unconscious person; seek medical attention.

TRANSPORT INFO:

Proper Shipping Name - Not Regulated for Transport by Truck

DOT Hazard Class - Not Regulated

Packing Group - Not Regulated

ID# - Not Regulated

**AVAILABLE IN:**

Gal. Jug, 5 Gal. Bucket, 55 Gal. Drum,
275 Gal. Tote, 300 Gal. Leg Tank or delivered via Tanker Truck



GUARANTEE: Jamson Labs' / Power Kleen's manufacturing and laboratory controls ensure uniform quality throughout our product line. All Jamson Labs / Power Kleen manufactured products are guaranteed for 1 year when used as directed.