

Directions:

CARPET STEAM EXTRACTORS: As a starting point add 1/2 to 1 ounce of defoamer to 10 gallons of waste solution tank capacity. Unusual jobs may require a second addition.

AUTOMATIC FLOOR SCRUBBERS: For foaming problems in waste solution tanks add 1 to 2 ounces of defoamer per 10 gallons of water in solution tank.

Gone

FOAM CONTROL CONCENTRATE

Multi-purpose industrial-grade concentrated defoamer

- NOW MORE STABLE AND LONGER LASTING
- FOR GENERAL USE IN HOT OR COLD SYSTEMS
- NO NEED TO SHAKE OR MIX DUE TO SEPARATION LIKE OTHER PRODUCTS!

1 Gal.
 5 Gal.
 55 Gal.
 275 Gal.

KEEP OUT OF REACH OF CHILDREN.
 DO NOT TAKE INTERNALLY.
 AVOID CONTACT WITH EYES.

Inhalation: None Expected. Remove affected person to fresh air; if symptoms persist seek medical attention.

Skin: None Expected. Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

Eyes: Check for and remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

Ingestion: Give two glasses of water for dilution; DO NOT induce vomiting; never give anything by mouth to an unconscious person; seek medical attention.

TRANSPORT INFORMATION:

Proper Shipping Name - Not Regulated for Transport by Truck
 DOT Hazard Class - Not Regulated
 Packing Group - Not Regulated
 ID# - None

PowerKleen
 Quality Chemicals • Superior Service

Power Kleen Corporation
 To Reorder, Call: (813) 854-2648
 FAX (813) 854-3133

In Case Of Chemical Emergency Contact
 Chem-Tel 24 Hours (800) 255-3924
www.PowerKleen.com