

PowerKleen
Quality Chemicals • Superior Service

POWERFAC 140 is specifically developed for use with steam cleaners and hot or cold pressure washing systems. Formulated for heavy duty industrial applications where a safer more powerful solvent is required. Non-flammable, non-toxic, and non-corrosive to metals.

-Delivers fast detergent penetration for speedy cleaning through power spray or steam cleaning devices.

-Many times more effective than typical cleaning compounds, even more so in hard water.

-Safe: Recommended for cleaning all metals including aluminum. Generally safe on sound industrial paint in recommended dilutions. Rinses easily.

-Versatile: Removes difficult to clean petroleum base and edible oil grime. Rapidly dissolves carbohydrate and protein soils. Use with steam, power spray, or manual swabbing. Clean equipment, floors, walls or any hard to clean surface.

-Overcomes hard water: For maximum detergency. Prohibits scale formation in steam cleaner coils.

-Economical: Every ounce bursting with

cleaning power. No fillers or inert ingredients. Unique formulation saves on material, but the real economy is getting the job done properly and fast.

Directions:

Follow the dilution table below. Apply the proper Powerfac 140 solution by spray. Brush or sponge, and allow solution to penetrate for several minutes. Rinse off thoroughly.

Dilution D: For heavy equipment and metal parts.

Dilution C: For marine equipment, fiberglass, and vinyls.

Dilution B: For all painted surfaces, plastic or wood.

Dilution A: For all vehicles, trucks or busses.

DILUTION TABLE

	A	B	C	D
Parts of Water	25	20	15	10
Parts of Powerfac	1	1	1	1

DANGER:

DO NOT TAKE INTERNALLY. HARMFUL IF SWALLOWED.

CAUTION: KEEP OUT OF REACH OF CHILDREN.

MAY CAUSE HARM TO PAINTED SURFACES IF NOT USED AS DIRECTED

Power Fac 140

HEAVY-DUTY CLEANER/DEGREASER

UNEQUALED HIGH-SPEED CLEANING POWER

- SUPERIOR CLEANING IN HOT OR COLD WATER
- CHEMICAL BREAK-THROUGH
- EXCLUSIVE FORMULATION
- NO BRUSHING NECESSARY
- DYNAMIC REMOVAL OF:
GREASE, GRIME, ROAD FILMS, BONDED SOILS

○ 1 Gal.

○ 5 Gal.

○ 55 Gal.

○ 275 Gal.



TRANSPORT INFORMATION:

Proper Shipping Name -
Corrosive Liquids, N.O.S.,
(Contains Potassium Hydroxide)
DOT Hazard Class - 8 Packing Group - III
ID# - UN 1760

Inhalation: Remove affected person to fresh air; wash mouth and nasal passages with water repeatedly; if breathing difficulties persist seek medical attention.

Skin: Remove contaminated clothing; wash affected area with soap and water; DO NOT attempt to neutralize with chemical agents; if irritation persists, seek medical attention. Launder contaminated clothing before reuse.

Eyes: Check for and remove any contact lenses. Immediately flush eyes with clear running water for 15 minutes while holding eyelids open. Seek medical attention immediately.

Ingestion: Drink two glasses of water followed by milk; give diluted vinegar or lemon juice to conscious person; DO NOT induce vomiting; seek medical attention immediately.

PowerKleen

Quality Chemicals • Superior Service

Power Kleen Corporation

To Reorder, Call: (813) 854-2648

FAX (813) 854-3133

In Case Of Chemical Emergency Contact

Chem-Tel 24 Hours (800) 255-3924

www.PowerKleen.com