

# Oxyphos

 - Metal Treatment / Phosphatizer**PRODUCT #:** PK-4900**CHARACTERISTICS:**

Appearance: Green Liquid  
 Odor: Characteristic  
 pH: <1.00  
 Specific Gravity: 1.254  
 Weight: 10.46  
 Viscosity: Water Like  
 Flash Point: N/A  
 Dilution: Ready To Use

**ADVANTAGES:**

Oxyphos is a professional-strength metal treatment phosphatizer. It chemically converts iron oxide (rust) to iron phosphate, creating a protective "chromated phosphate" coating. It prevents subsequent rust, improves adherence, and extends the life of the paint film.

**DIRECTIONS:**

Loosen any corrosion with a wire brush. If the surface is greasy, remove with a solvent. Apply Oxyphos to all exposed areas. If there are pitted areas, concentrate on them. Use a brush, roller, sprayer or dipping system. Allow a minimum of (1) one hour for conversion to be accomplished (until surface turns gray or black). When conversion is completed, the surface will have a slight tackiness, ideal for accepting a coating.

**PRECAUTIONS:**

**Inhalation:** Remove affected person to fresh air; if breathing difficulties persist seek medical attention.

**Skin:** Remove contaminated clothing; wash affected area with soap and water; DO NOT attempt to neutralize with chemical agents; if irritation persists, seek medical attention. Launder contaminated clothing before reuse.

**Eyes:** Check for and remove any contact lenses. Immediately flush eyes with clear running water for 15 minutes while holding eyelids open. Seek medical attention immediately.

**Ingestion:** Drink two glasses of water followed by milk, milk of magnesia or other non-alcoholic liquids to conscious person; DO NOT induce vomiting; seek medical attention immediately.

**TRANSPORT INFORMATION:**

Proper Shipping Name - Compounds, Cleaning Liquid  
 (Phosphoric Acid)  
 DOT Hazard Class - 8  
 Packing Group - III  
 ID# - UN 1760

**GUARANTEE:** Jamson Labs' / Power Kleen's manufacturing and laboratory controls ensure uniform quality throughout our product line. All Jamson Labs / Power Kleen manufactured products are guaranteed for 1 year when used as directed.

**AVAILABLE IN:**

Gal. Jug, 5 Gal. Bucket, 55 Gal. Drum,  
 275 Gal. Tote, 300 Gal. Leg Tank or delivered via Tanker Truck

