

Directions:

- Mix 1 gallon of product with 35 gallons of water and apply as a thick foam through a foaming device.
- For the beds of trucks carrying asphalt, apply liberally to the truck bed.
- May be used in stronger concentrations if desired to increase residual effect.
- To prevent adhesion of mix to equipment or hand tools, apply the solution by spray or immersion.
- This product will not adversely affect asphalt when used as directed.

Bio Release

FOAMING ASPHALT RELEASE AGENT

CONCENTRATED BLEND

A CONCENTRATED BLEND OF GREASE EMULSIFYING,
 SOIL-SUSPENDING AND WATER CONDITIONING AGENTS
 DESIGNED TO COAT ALL SURFACES THAT MAY COME IN
 CONTACT WITH TRUCK BEDS

KEEP OUT OF REACH OF CHILDREN.
 DO NOT TAKE INTERNALLY.
 AVOID CONTACT WITH EYES.

1 Gal. 5 Gal. 55 Gal. 275 Gal.

Inhalation: None Expected. Remove affected person to fresh air; if symptoms persist seek medical attention.

Skin: None Expected. Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

Eyes: Check for and remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

Ingestion: Give two glasses of water for dilution; DO NOT induce vomiting; never give anything by mouth to an unconscious person; seek medical attention.

TRANSPORT INFORMATION:

Proper Shipping Name - Not Regulated for Transport by Truck
 DOT Hazard Class - Not Regulated
 Packing Group - Not Regulated
 ID# - None

PowerKleen
 Quality Chemicals • Superior Service

Power Kleen Corporation
 To Reorder, Call: (813) 854-2648
 FAX (813) 854-3133

In Case Of Chemical Emergency Contact
 Chem-Tel 24 Hours (800) 255-3924
www.PowerKleen.com