



Jamson Labs

Quality Chemicals Since 1973



TRANSPORT INFORMATION:

Proper Shipping Name -
Dichloromethane Mixture
DOT Hazard Class - 6.1
Packing Group - PG III
ID# - UN 1593

Inhalation: Remove affected person to fresh air; if not breathing, administer CPR and seek medical attention.

Skin: Remove contaminated clothing; wash affected area with soap and water; DO NOT attempt to neutralize with chemical agents; if irritation persists, seek medical attention. Launder contaminated clothing before reuse.

Eyes: Check for and remove any contact lenses. Immediately flush eyes with clear running water for 15 minutes while holding eyelids open. Seek medical attention immediately.

Ingestion: Drink two glasses of water to conscious person; DO NOT induce vomiting; seek medical attention immediately.



Jamson Labs

Quality Chemicals Since 1973

Jamson Laboratories Inc.

(813) 855-4565

FAX (813) 854-3133

In Case Of Chemical Emergency Contact

Chem-Tel 24 Hours (800) 255-3924

Paint Remover

ULTRA FAST & EFFECTIVE PAINT STRIPPER

Professional Strength Formulation

- **FAST, EFFECTIVE PAINT REMOVER/STRIPPER**
- **QUICK DRYING TIME**
- **CAN BE APPLIED BOTH MANUALLY OR IN A FLOW-OVER SYSTEM**

- 1 Gal.**
- 5 Gal.**
- 55 Gal.**
- 275 Gal.**

concentrated. **DO NOT CUT OR WELD CONTAINER** due to explosion hazard. **FOR SPILLS**, use proper protective equipment. For small spills use sorbent, allow to stand, then sweep into airtight container for disposal. For large spills, evacuate the area, dike, then pump into containers for disposal. **NOTE:** This product repacked for consumer markets may require labeling different than give on this container.

INHALATION PRECAUTIONS: High concentrations of vapors can accumulate in low areas. Progressively higher exposure levels over 1000 ppm can cause dizziness, drunkenness, unconsciousness or even **DEATH**. **EXTREMELY** high vapor concentrations (over 10,000 ppm) are immediately **HAZARDOUS TO LIFE**. **CONTINUED EXPOSURE SHOULD NOT EXCEED OSHA 8-HOUR TWA**. Repeated and prolonged exposure to vapor concentrations at or above where physical effects begin (dizziness, eye irritation) may be hazardous to health.

EXPOSURE LIMITS-PARTS PER MILLION (PPM) OSHA: 8-HOUR TWA: 500 PPM

DANGER:
DO NOT TAKE INTERNALLY. HARMFUL IF INHALED OR SWALLOWED.
CAUTION: KEEP OUT OF REACH OF CHILDREN.

Directions:

- Manual application: Brush onto surface with a paintbrush or rag. Wet thoroughly. Allow to stand for 30 seconds to 2 minutes. Product should be visibly working almost immediately. Use a brush or rag to “peel” off paint or varnish and allow to air dry. If there is any paint remaining on the surface. Apply again only in those areas.

- Flow Over System: submerge surface in the tank of DC-141 and allow to sit for approximately 2 minutes. Remove surface from tank and allow to stand for another 1 minute. Exposure to air will help the process. Use a brush or rag to “peel” off any remaining paint or varnish and allow to air dry. If there is any paint remaining on the surface. Apply again only in those areas or re-submerge.

HANDLING & STORAGE

Vapors of product are heavier than air and will collect in low areas such as pits, degreasers, storage tanks, and other confined areas. Do not enter these areas where vapors or Methylene Chloride are suspected unless special breathing apparatus is used and observer is present for assistance. Liquid and vapor of this product can decompose to harmful and corrosive vapors when in contact with flame and other ignition sources. In addition, this product may develop a flammable atmosphere in confined areas. **KEEP AWAY FROM FLAMES AND OTHER IGNITION SOURCES**, such as welding, when used where vapors may become