Power Kleen

Safety Data Sheet acc. to OSHA HCS

Printing date 11/04/2014 Reviewed on 02/11/2014

Jamson Labs

Chemical Solutions Since 1973

1 Identification

· Product identifier


· Trade name: Pronto

· Article number: 6514 PK

· Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Power Kleen Corporation 101 South Bayview Blvd. OLDSMAR, FL 34677

USA



· Emergency telephone number: ChemTel Inc. (800) 255-3924 Intl. +01 (813) 248-0585

2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:

disodium metasilicate

· Hazard statements

Causes skin irritation.

Causes serious eve damage.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Wear protective gloves/protective clothing/eye protection/face protection.

Wash thoroughly after handling.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Take off contaminated clothing and wash before reuse.

(Contd. on page 2)

Printing date 11/04/2014 Reviewed on 02/11/2014

Trade name: Pronto

(Contd. of page 1)

If skin irritation occurs: Get medical advice/attention.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
6834-92-0	disodium metasilicate	2.5-10%
66455-15-0	C10-12 6 Mole Linear Alcohol Ethoxylate	≤ 2.5%
1310-73-2	sodium hydroxide	≤ 2.5%

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Remove contact lenses if able to do so.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

· Most important symptoms and effects, both acute and delayed

Nausea

Corrosive and extremely irritating to all tissues.

Cramp

Gastric or intestinal disorders

(Contd. on page 3)

Printing date 11/04/2014 Reviewed on 02/11/2014

Trade name: Pronto

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Unsuitable material for receptacle: aluminium.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

1310-73-2 sodium hydroxide

PEL Long-term value: 2 mg/m³ REL Ceiling limit value: 2 mg/m³

(Contd. on page 4)

(Contd. of page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 11/04/2014 Reviewed on 02/11/2014

Trade name: Pronto

TLV Ceiling limit value: 2 mg/m³

· Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Neoprene gloves

PVC or PE gloves

Butyl rubber, BR

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Not suitable are gloves made of the following materials:

Strong gloves

Leather gloves

· Eye protection:



Tightly sealed goggles

· Body protection:

Apron

Alkaline resistant protective clothing

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid Color: Green

(Contd. on page 5)

Printing date 11/04/2014 Reviewed on 02/11/2014

Trade name: Pronto

	(Conto	l. of pag
Odor:	Sassafras	
Odour threshold:	Not determined.	
pH-value at 20 °C (68 °F):	10.5	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:		
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure:	Not determined.	
Density at 20 °C (68 °F):	1.03 g/cm³ (8.595 lbs/gal)	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/wat	t er): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	0.9 %	
Water:	92.1 %	
VOC content:	3.2 %	
	9.7 g/l / 0.08 lb/gl	
Solids content:	4.7 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Reacts with strong acids and oxidizing agents.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:

Sodium Oxides

(Contd. on page 6)

Printing date 11/04/2014 Reviewed on 02/11/2014

Trade name: Pronto

Carbon monoxide and carbon dioxide

(Contd. of page 5)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

 $The \ product \ shows \ the \ following \ dangers \ according \ to \ internally \ approved \ calculation \ methods \ for \ preparations:$

Harmful

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
67-63-0 propan-2-ol	3	
111-76-2 2-butoxyethanol	3	
· NTP (National Toxicology Program)		
None of the ingredients is listed.		
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 7)

Printing date 11/04/2014 Reviewed on 02/11/2014

Trade name: Pronto

· Recommended cleansing agent: Water, if necessary with cleansing agents.

(Contd. of page 6)

UN-Number	
DOT, IMDG, IATA	UN3266
UN proper shipping name	
DOT	Corrosive liquid, basic, inorganic, n.o.s. (Sodium hydroxide
IMDG, IATA	Disodium trioxosilicate) CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (SODIUI HYDROXIDE, DISODIUM TRIOXOSILICATE)
Transport hazard class(es)	
DOT	
~ ·	
CORROSIVE	
•	
Class	8 Corrosive substances
Label	8
IMDG, IATA	
Class	8 Corrosive substances
Label	8
Packing group	
DOT, IMDG, IATA	III
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	
Danger code (Kemler):	80
EMS Number:	F-A,S-B
Segregation groups	Alkalis
Transport in bulk according to Annex	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	5L

Printing date 11/04/2014 Reviewed on 02/11/2014

Trade name: Pronto

	(Contd. of page 7
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN3266, Corrosive liquid, basic, inorganic, n.o.s. (Sodium
G	hydroxide, Disodium trioxosilicate), 8, III

	hydroxide, Disodium trioxosilicate), 8, III	
5 Regulator	y information	
· Safety, heal	th and environmental regulations/legislation specific for the substance or mixture	
· Sara		
	(extremely hazardous substances):	
None of the	None of the ingredients is listed.	
	(Specific toxic chemical listings):	
	pentasodium triphosphate	
-	propan-2-ol	
	2-butoxyethanol	
67-56-1	nethanol	
· TSCA (Toxi	ic Substances Control Act):	
	disodium metasilicate	
	C10-12 6 Mole Linear Alcohol Ethoxylate	
	pentasodium triphosphate	
	propan-2-ol	
	sodium hydroxide	
	Disodium cocoamphodipropionate	
	2-butoxyethanol	
	tetrasodium ethylenediaminetetraacetate	
	methanol	
	water, distilled, conductivity or of similar purity	
· Proposition		
	known to cause cancer:	
	ingredients is listed.	
	known to cause reproductive toxicity for females:	
None of the	ingredients is listed.	
· Chemicalsk	nown to cause reproductive toxicity for males.	
None of the	ingredients is listed.	
· Chemicals k	known to cause developmental toxicity:	
67-56-1 me		
· Carcinogen	ic categories	
· EPA (Envir	onmental Protection Agency)	

·EPA	(Environmental Protection Agency)

111-76-2 2-butoxyethanol NL

· TLV (Threshold Limit Value established by ACGIH)

67-63-0 propan-2-ol

(Contd. on page 9)

A4

Printing date 11/04/2014 Reviewed on 02/11/2014

Trade name: Pronto

(Contd. of page 8)

111-76-2 2-butoxyethanol

A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labeling:

disodium metasilicate

· Hazard statements

Causes skin irritation.

Causes serious eye damage.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Wear protective gloves/protective clothing/eye protection/face protection.

Wash thoroughly after handling.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Take off contaminated clothing and wash before reuse.

If skin irritation occurs: Get medical advice/attention.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. 02/11/2014

- · Department issuing MSDS: Environment protection department.
- · Date of preparation / last revision

11/04/2014 / -

02/11/2014

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1