

Directions:

For hand washing:

- Dilute 10 parts water to 1 part Cab Wash in a wash bucket.
- Brush the entire truck starting from the roof and working down to the wheels.
- Rinse thoroughly and allow to air dry.

For automatic, coin operated, or high pressure cleaning systems:

- Use one ounce to one gallon of water.
- Automatic recycling car wash systems should use only one half gallon of product to each five hundred gallons of water in the holding tank. This dilution will give an abundance of suds and ensure long brush life.

KEEP OUT OF REACH OF CHILDREN.
 DO NOT TAKE INTERNALLY.
 AVOID CONTACT WITH EYES.

Cab Wash

HIGH-LUBRICITY TRUCK CLEANER

EXCELLENT FOR HEAVY ROAD FILM

- FOR HAND WASHING
OR HIGH PRESSURE CLEANING SYSTEMS
- SAFE ON WINDSHIELDS
 - SAFE ON PAINTS
 - NON-CORROSIVE
- FORTIFIED FOR LONG-LASTING SUDS

1 Gal. 5 Gal. 55 Gal. 275 Gal.

Inhalation: None Expected. Remove affected person to fresh air; if symptoms persist seek medical attention.

Skin: None Expected. Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

Eyes: Check for and remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

Ingestion: Give two glasses of water for dilution; DO NOT induce vomiting; never give anything by mouth to an unconscious person; seek medical attention.

TRANSPORT INFORMATION:

Proper Shipping Name - Not Regulated for Transport by Truck
 DOT Hazard Class - Not Regulated
 Packing Group - Not Regulated
 ID# - None

PowerKleen
 Quality Chemicals • Superior Service

Power Kleen Corporation
 To Reorder, Call: (813) 854-2648
 FAX (813) 854-3133

In Case Of Chemical Emergency Contact
 Chem-Tel 24 Hours (800) 255-3924
www.PowerKleen.com