PowerKleen

Safety Data Sheet acc. to OSHA HCS

Printing date 11/05/2014 Reviewed on 07/02/2014

Jamson Labs

Chemical Solutions Since 1973

1 Identification

· Product identifier


· Trade name: Scrub It (Non Butyl)

· Article number: 6597 PK

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Power Kleen Corporation 101 South Bayview Blvd. OLDSMAR, FL 34677

USA



· Emergency telephone number: ChemTel Inc. (800) 255-3924 Intl. +01 (813) 248-0585

2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:

disodium metasilicate

· Hazard statements

Causes severe skin burns and eye damage.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Do not breathe dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

- USA

(Contd. of page 1)

Safety Data Sheet acc. to OSHA HCS

Printing date 11/05/2014 Reviewed on 07/02/2014

Trade name: Scrub It (Non Butyl)

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 4 Fire = 0 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
6834-92-0	disodium metasilicate	2.5-10%
66455-15-0	C10-12 6 Mole Linear Alcohol Ethoxylate	≤2.5%
67-63-0	propan-2-ol	≤ 2.5%
1310-73-2	sodium hydroxide	≤ 2.5%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Remove contact lenses if able to do so.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

· Most important symptoms and effects, both acute and delayed

Corrosive and extremely irritating to all tissues.

Nausea

Gastric or intestinal disorders

Cramp

· Danger Danger of gastric perforation.

(Contd. on page 3)

Printing date 11/05/2014 Reviewed on 07/02/2014

Trade name: Scrub It (Non Butyl)

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed Medical supervision for at least 48 hours.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Unsuitable material for receptacle: glass or ceramic.

Unsuitable material for receptacle: aluminium.

· Information about storage in one common storage facility:

Store away from oxidizing agents.

Store away from foodstuffs.

- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

Printing date 11/05/2014 Reviewed on 07/02/2014

Trade name: Scrub It (Non Butyl)

(Contd. of page 3)

· Control parameters

Control parameters			
· Components with limit values that require monitoring at the workplace:			
<i>67-6</i> .	67-63-0 propan-2-ol		
PEL	Long-term value: 980 mg/m³, 400 ppm		
REL	Short-term value: 1225 mg/m³, 500 ppm		
	Long-term value: 980 mg/m³, 400 ppm		
TLV	Short-term value: 984 mg/m³, 400 ppm		
	Long-term value: 492 mg/m³, 200 ppm		
	BEI		
1310	-73-2 sodium hydroxide		
PEL	Long-term value: 2 mg/m³		
REL	Ceiling limit value: 2 mg/m³		
TLV	Ceiling limit value: 2 mg/m³		
· Ingredients with biological limit values:			
67-63-0 propan-2-ol			
BEI	40 mg/L		
	Medium: urine		

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Time: end of shift at end of workweek

Immediately remove all soiled and contaminated clothing.

Parameter: Acetone (background, nonspecific)

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Neoprene gloves

PVC or PE gloves

Nitrile rubber, NBR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Printing date 11/05/2014 Reviewed on 07/02/2014

Trade name: Scrub It (Non Butyl)

· Eye protection:

(Contd. of page 4)



Tightly sealed goggles

· Body protection: Alkaline resistant protective clothing

Odour threshold: pH-value at 20 °C (68 °F): Change in condition Melting point/Melting range: Boiling point/Boiling range: 100 Flash point: Not Ignition temperature: Decomposition temperature: Not Auto igniting: Pro Explosion limits: Lower: Upper: Not Vapor pressure: Not Relative density Not 13. Not 13. Not Not Not Not 100 100 100 100 100 100 100 1	uid e aracteristic determined. 8 determined. °C (212 °F) applicable. applicable. determined. duct is not selfigniting. duct does not present an explosion hazard. determined.
Appearance: Form: Color: Blu Color: Odour threshold: Not PH-value at 20 °C (68 °F): 13. Change in condition Melting point/Melting range: Boiling point/Boiling range: Not Flash point: Not Ignition temperature: Decomposition temperature: Not Auto igniting: Pro Explosion limits: Lower: Upper: Not Vapor pressure: Not Relative density Not	e aracteristic determined. 8 determined. o C (212 °F) applicable. applicable. determined. duct is not selfigniting. duct does not present an explosion hazard. determined. determined.
Form: Color: Blu Color: Odour threshold: PH-value at 20 °C (68 °F): Change in condition Melting point/Melting range: Boiling point/Boiling range: Indicate the state of the	e aracteristic determined. 8 determined. o C (212 °F) applicable. applicable. determined. duct is not selfigniting. duct does not present an explosion hazard. determined. determined.
Odor: Odour threshold: Not PH-value at 20 °C (68 °F): 13. Change in condition Melting point/Melting range: Boiling point/Boiling range: 100 Flash point: Not Flammability (solid, gaseous): Not Ignition temperature: Not Auto igniting: Pro Explosion limits: Lower: Upper: Not Vapor pressure: Not Relative density Not	determined. determined. determined. C (212 °F) applicable. applicable. determined. determined. duct is not selfigniting. duct does not present an explosion hazard. determined.
Odour threshold: pH-value at 20 °C (68 °F): 13. Change in condition Melting point/Melting range: Boiling point/Boiling range: 100 Flash point: Not Ignition temperature: Decomposition temperature: Not Auto igniting: Pro Explosion limits: Lower: Upper: Not Vapor pressure: Not Relative density Not 13. Not Not Not Not 100 Not Not Not Not Not Not Not N	determined. determined. o C (212 °F) applicable. applicable. determined. duct is not selfigniting. duct does not present an explosion hazard. determined.
pH-value at 20 °C (68 °F): Change in condition Melting point/Melting range: Boiling point/Boiling range: 100 Flash point: Not Flammability (solid, gaseous): Not Ignition temperature: Decomposition temperature: Not Auto igniting: Pro Explosion limits: Lower: Upper: Not Vapor pressure: Not Density at 20 °C (68 °F): Relative density Not	determined. o C (212 °F) applicable. applicable. determined. duct is not selfigniting. duct does not present an explosion hazard. determined.
Change in condition Melting point/Melting range: Boiling point/Boiling range: 100 Flash point: Not Flammability (solid, gaseous): Not Ignition temperature: Not Auto igniting: Pro Explosion limits: Lower: Upper: Not Vapor pressure: Not Relative density Not	determined. °C (212 °F) applicable. applicable. determined. duct is not selfigniting. duct does not present an explosion hazard. determined.
Melting point/Melting range: Boiling point/Boiling range: 100 Flash point: Not Flammability (solid, gaseous): Not Ignition temperature: Decomposition temperature: Not Auto igniting: Pro Explosion limits: Lower: Upper: Not Vapor pressure: Not Relative density Not	applicable. applicable. determined. duct is not selfigniting. duct does not present an explosion hazard. determined.
Boiling point/Boiling range: 100 Flash point: Not Flammability (solid, gaseous): Not Ignition temperature: Not Auto igniting: Pro Danger of explosion: Pro Explosion limits: Lower: Not Upper: Not Vapor pressure: Not Density at 20 °C (68 °F): 1.00 Relative density	applicable. applicable. determined. duct is not selfigniting. duct does not present an explosion hazard. determined.
Flash point: Note Flammability (solid, gaseous): Note Ignition temperature: Note Auto igniting: Pro Danger of explosion: Pro Explosion limits: Lower: Note Upper: Note Vapor pressure: Note Density at 20 °C (68 °F): 1.00 Relative density	applicable. applicable. determined. duct is not selfigniting. duct does not present an explosion hazard. determined.
Flammability (solid, gaseous): Note Ignition temperature: Decomposition temperature: Note Ignition temperature:	applicable. determined. duct is not selfigniting. duct does not present an explosion hazard. determined.
Ignition temperature: Decomposition temperature: Note that the proof of the proof	determined. duct is not selfigniting. duct does not present an explosion hazard. determined.
Decomposition temperature: Note Auto igniting: Pro Danger of explosion: Pro Explosion limits: Lower: Note Upper: Note Vapor pressure: Note Density at 20 °C (68 °F): 1.00 Relative density Note	duct is not selfigniting. duct does not present an explosion hazard. determined.
Auto igniting: Pro Danger of explosion: Pro Explosion limits: Lower: Not Upper: Not Vapor pressure: Not Density at 20 °C (68 °F): 1.00 Relative density Not	duct is not selfigniting. duct does not present an explosion hazard. determined.
Danger of explosion: Explosion limits: Lower: Not Upper: Not Vapor pressure: Not Density at 20 °C (68 °F): Relative density Not	duct does not present an explosion hazard. determined.
Explosion limits: Lower: Not Upper: Not Vapor pressure: Not Density at 20 °C (68 °F): 1.0. Relative density Not	determined.
Lower: Not Upper: Not Vapor pressure: Not Density at 20 °C (68 °F): 1.0 Relative density Not	
Upper: Non Vapor pressure: Non Density at 20 °C (68 °F): 1.00 Relative density Non	
Vapor pressure: Note Density at 20 °C (68 °F): Relative density Note	
Density at 20 °C (68 °F): 1.0. Relative density Not	determined.
Relative density Not	determined.
	3 g/cm³ (8.595 lbs/gal)
	determined.
·······································	determined.
	determined.
Solubility in / Miscibility with	
Water: Ful	ly miscible.
Partition coefficient (n-octanol/water): Not	determined.
Viscosity:	
- 5	determined.
Kinematic: Not	determined.
Solvent content:	
Organic solvents: 1.0 Water: 89.	%

(Contd. on page 6)

Reviewed on 07/02/2014 Printing date 11/05/2014

Trade name: Scrub It (Non Butyl)

	(Contd. of page 5)
VOC content:	1.0 %
	10.6 g/l / 0.09 lb/gl
Solids content:	9.2 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions

Reacts with strong acids and oxidizing agents.

Corrodes aluminium.

- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:

Phosphorus oxides (e.g. P2O5)

Nitrogen oxides

Sodium Oxides

Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Strong caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
67-63-0 propan-2-ol	3
· NTP (National Toxicology Program)	
None of the ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

Printing date 11/05/2014 Reviewed on 07/02/2014

Trade name: Scrub It (Non Butyl)

(Contd. of page 6)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even extremely small quantities leak into the ground.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· UN-Number	
· DOT. IMDG. IATA	UN3266

· UN proper shipping name

DOT Corrosive liquid, basic, inorganic, n.o.s. (Sodium hydroxide,

Disodium trioxosilicate)

· IMDG, IATA CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (SODIUM HYDROXIDE, DISODIUM TRIOXOSILICATE)

- · Transport hazard class(es)
- $\cdot DOT$



· Class 8 Corrosive substances

(Contd. on page 8)

Printing date 11/05/2014 Reviewed on 07/02/2014

Trade name: Scrub It (Non Butyl)

	(Contd. of page
Label	8
IMDG, IATA	
8	
Class	8 Corrosive substances
Label	8
Packing group	
DOT, IMDG, IATA	III
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	
Danger code (Kemler):	80
EMS Number:	F- A , S - B
Segregation groups	Alkalis
Transport in bulk according to Annex	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
· IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN3266, Corrosive liquid, basic, inorganic, n.o.s. (Sodiu
-	hydroxide, Disodium trioxosilicate), 8, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

67-63-0 propan-2-ol

7758-29-4 pentasodium triphosphate

· TSCA (Toxic Substances Control Act):

6834-92-0 disodium metasilicate

66455-15-0 C10-12 6 Mole Linear Alcohol Ethoxylate

67-63-0 propan-2-ol

7758-29-4 pentasodium triphosphate

(Contd. on page 9)

Printing date 11/05/2014 Reviewed on 07/02/2014

Trade name: Scrub It (Non Butyl)

	(Contd. of page 8)
1310-73-2	sodium hydroxide
68604-71-7	Disodium cocoamphodipropionate
64-02-8	tetrasodium ethylenediaminetetraacetate
7732-18-5	water, distilled, conductivity or of similar purity

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicalsknown to cause reproductive toxicity for males.

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

67-63-0 propan-2-ol

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling:

disodium metasilicate

· Hazard statements

Causes severe skin burns and eye damage.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Do not breathe dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

USA

Printing date 11/05/2014 Reviewed on 07/02/2014

Trade name: Scrub It (Non Butyl)

(Contd. of page 9)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Environment protection department.
- · Date of preparation / last revision

11/05/2014 / -

7/2/2014

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

USA