

Super Fallout Remover - Metal Fallout Particle Remover

PRODUCT #: PK-7011

CHARACTERISTICS:

Appearance: Green Liquid
 Odor: Characteristic
 pH: 1.80
 Specific Gravity: 1.098
 Weight: 9.16
 Viscosity: Water Like
 Flash Point: N/A
 Dilution: 1:1



ADVANTAGES:

This is an industrial-strength particle remover for efficiently removing metal fallout from painted surfaces.

DIRECTIONS:

Wet surface thoroughly with water before treating. Mix minimum of 50-50 with water and apply on surface no more than two (2) minutes in order for chemical to penetrate. DO NOT allow chemical to dry on surface. To help speed operation on heavily affected areas, agitate with towel, soft brush or sponge. Rinse thoroughly with pressure washer.

PRECAUTIONS:

Inhalation: Remove affected person to fresh air; wash mouth & nasal passages with water repeatedly. If breathing difficulty persists, seek medical attention.

Skin: Remove contaminated clothing; wash affected area with soap and water; if irritation persists, seek medical attention. DO NOT attempt to neutralize with chemical agents. Launder contaminated clothing before reuse.

Eyes: Remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; get medical attention immediately.

Ingestion: Drink large quantities of water or milk; DO NOT induce vomiting; seek medical attention.

TRANSPORT INFO:

Proper Shipping Name - Compounds, Cleaning Liquid, N.O.S., (Contains Oxalic Acid)
 DOT Hazard Class - 8
 Packing Group - III
 ID# - UN 1760



AVAILABLE IN:

Gal. Jug, 5 Gal. Bucket, 55 Gal. Drum,
 275 Gal. Tote, 300 Gal. Leg Tank or delivered via Tanker Truck



GUARANTEE: Jamson Labs' / Power Kleen's manufacturing and laboratory controls ensure uniform quality throughout our product line. All Jamson Labs / Power Kleen manufactured products are guaranteed for 1 year when used as directed.