

# Vinyl Top Dressing - Vinyl Protectant

**PRODUCT #:** PK-7020**TRANSPORT INFO:**

Proper Shipping Name - Not Regulated for Transport by Truck

DOT Hazard Class - Not Regulated

Packing Group - Not Regulated

ID# - None

**CHARACTERISTICS:**

Appearance: Milky Liquid  
 Odor: Acrylic  
 pH: N/A  
 Specific Gravity: 0.990  
 Weight: 8.26  
 Viscosity: Water Like  
 Flash Point: N/A  
 Dilution: Ready To Use

**ADVANTAGES:**

This is a professional-grade vinyl protectant / beautifier. The glossy, detergent resistant protective coating is designed to restore a "like new" appearance to vinyl on car tops, trim, trailers and mobile homes. The coating is also clear, non-yellowing and is also detergent resistant to retain its glossy appearance through many washings with non-ammoniated cleaners. It can be easily removed by stripping with ammoniated detergents

**DIRECTIONS:**

**PREPARATION:** Thoroughly Clean vinyl surface of soils, stains, and previous protective coatings by scrubbing with a strong solution of butyl cleaner and ammonia. Problem surfaces may require spot bleaching to remove stubborn stains. Rinse well and allow to dry for at least 30 minutes.

**COVERAGE:** 1 gallon per 3,000 - 4,000 square feet will single coat 100 - 150 car tops.

**APPLICATION:** Apply to cool surface only. If surface is sun hot, wet down to cool, let dry and apply. Thoroughly saturate a sponge or swab with dressing. Apply in smooth even strokes to surface. Do not scrub back and forth to try to rub in. Avoid making foam. Allow to dry for 30 minutes, and apply a second coat.

**TO CLEAN:** Pressure wash or lightly scrub using a general car washing cleaner. Rinse well.

**TO STRIP:** Scrub with regular cleaning solution to which 1 cup of household ammonia has been added per gallon of solution. Rinse well.

**PRECAUTIONS:**

**Inhalation:** None Expected. Remove affected person to fresh air; if symptoms persist seek medical attention.

**Skin:** None Expected. Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

**Eyes:** Check for and remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

**Ingestion:** Give two glasses of water for dilution; DO NOT induce vomiting; never give anything by mouth to an unconscious person; seek medical attention.

**AVAILABLE IN:**

Gal. Jug, 5 Gal. Bucket, 55 Gal. Drum,  
 275 Gal. Tote, 300 Gal. Leg Tank or delivered via Tanker Truck



**GUARANTEE:** Jamson Labs' / Power Kleen's manufacturing and laboratory controls ensure uniform quality throughout our product line. All Jamson Labs / Power Kleen manufactured products are guaranteed for 1 year when used as directed.