

# Tar & Asphalt Remover

**PRODUCT #:** PK-7035

## CHARACTERISTICS:

Appearance: Amber Liquid  
 Odor: Solvent  
 pH: N/A  
 Specific Gravity: 0.818  
 Weight: 6.82  
 Viscosity: Water Like  
 Flash Point: N/A  
 Dilution: Ready To Use

## ADVANTAGES:

This product is an industrial-grade asphalt and tar remover. It is a blend of aliphatic and aromatic hydrocarbons with emulsifiers developed to minimize the costly time and clean up operations formerly required to restore vehicles and equipment contaminated with tar, bitumen, asphalt, stains, grease and sludge. This product is non-corrosive and will not harm any metal surfaces, contains no acid or alkalis. May be used in virtually any industry where asphalt, tar, grease or sludge are a problem. Minimize the costly time and clean up operations formerly required to restore vehicles and equipment contaminated with tar, bitumen, asphalt, stains, grease and sludge.

## DIRECTIONS:

Apply undiluted by brush or sprayer. Allow it to penetrate and dissolve for at least five minutes. Flush with water under pressure. Heavier deposits will require longer soaking and light brushing. Avoid prolonged contact with rubber and painted surfaces.

## PRECAUTIONS:

**Inhalation:** Remove affected person to fresh air; provide oxygen if breathing is difficult; if affected person is not breathing, administer CPR and seek emergency medical attention.

**Skin:** Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

**Eyes:** Check for and remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

**Ingestion:** DO NOT induce vomiting; if vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs; seek immediate medical attention. Vomiting may be induced only under the supervision of a physician.

## TRANSPORT INFO:

Proper Shipping Name - Not Regulated for Transport by Truck  
 DOT Hazard Class - Not Regulated  
 Packing Group - Not Regulated  
 ID# - Not Regulated

**GUARANTEE:** Jamson Labs' / Power Kleen's manufacturing and laboratory controls ensure uniform quality throughout our product line. All Jamson Labs / Power Kleen manufactured products are guaranteed for 1 year when used as directed.



## AVAILABLE IN:

Gal. Jug, 5 Gal. Bucket, 55 Gal. Drum,  
 275 Gal. Tote, 300 Gal. Leg Tank or delivered via Tanker Truck

