

# Diesel Fuel Treatment & Conditioner

**PRODUCT #:** PK-7055

**CHARACTERISTICS:**

Appearance: Clear Liquid  
 Odor: Floral  
 pH: N/A  
 Specific Gravity: 0.790  
 Weight: 6.59  
 Viscosity: Water Like  
 Flash Point: N/A  
 Dilution: Ready To Use

**TRANSPORT INFO:**

Proper Shipping Name: Flammable Liquid, N.O.S.,  
 (Isopropyl Alcohol)  
 DOT Hazard Class: 3  
 Packing Group: III  
 ID#: UN 1993



**ADVANTAGES:**

Diesel Fuel Treatment is a professional-grade organic concentrate blend that cleans, conditions and converts sludge into usable fuel. It eliminates storage problems, gum formation fuel degradation, water accumulation, and corrosion and can be used with interior mold & bacteria form floating organic masses. It helps clean dirty systems, sticky fuel injectors, stopped fuel lines, filters and de-foul pumps. Diesel Fuel Treatment also increases efficiency and aids in combustion insuring a hotter, cleaner flame while decreasing exhaust smoke. It reduces heavy oil burning point and is compatible with all common fuel oils numbers 1-6.

**DIRECTIONS:**

**For storage tanks:** add 1½ quarts of treatment and conditioner per 1000 gallons fuel capacity. To insure complete mixing add conditioner prior to fuel delivery. After initial conditioning add only 1 quart per 1000 gallons. Some areas may require slightly higher levels because of excessive heat and humidity.

**PRECAUTIONS:**

Vapors form explosive mixtures with air. Keep away from heat, sparks, flame, pilot lights and other ignition sources. Use only with adequate ventilation. Store in flammable label area. Container and equipment used for handling, storage or transfer must be grounded and bonded. This product is not suitable as a general purpose cleaner because of its flammability.

Do not get in eyes. Wear chemical splash goggles and other necessary protective equipment. Avoid contact with skin and clothing. Wear impervious gloves and other necessary protective equipment. Avoid breathing vapor or mist. Use only with adequate ventilation. Do not taste or swallow.

Use or store with adequate ventilation. Keep workplace airborne concentrations below legal and recommended limits. Circumstances could require use of respiratory protection. Refer to applicable OSHA regulations.

Wash thoroughly after handling. Do not transfer to unmarked container. Keep container closed when not in use. Loosen closure carefully. Do not use pressure to empty. Empty containers may contain hazardous product residues.



**AVAILABLE IN:**

Gal. Jug, 5 Gal. Bucket, 55 Gal. Drum,  
 275 Gal. Tote, 300 Gal. Leg Tank or delivered via Tanker Truck



**GUARANTEE:** Jamson Labs' / Power Kleen's manufacturing and laboratory controls ensure uniform quality throughout our product line. All Jamson Labs / Power Kleen manufactured products are guaranteed for 1 year when used as directed.