

Directions:

Only 1 gallon is used to 40 gallons of water. This will provide a high lubricity foam shield which prevents adhesion of asphalt to truck beds and sides.

This product is designed exclusively for industrial and institutional use by trained personnel. This product is sold "as is" and the manufacturer makes no warranty, express or implied, of merchantability, fitness for a particular purpose otherwise.

EXPOSURE: Overexposure and toxicity depend upon duration of exposure. Symptoms of overexposure include dizziness, nausea, headache, and even loss of consciousness. Aspiration may be a hazard. May be harmful or fatal if swallowed.

SAFETY CAUTION: It is recommended that protective gloves and safety glasses be worn when using this product. Make sure there is adequate ventilation. Refer to M.S.D.S. For additional information.

STORAGE: Store in a cool dry place away from all ignition sources. Keep container closed when not in use.

**CAUTION
FOR INDUSTRIAL USE ONLY**

Solvent Asphalt Release

ASPHALT & TAR DISPENSING AGENT

40X CONCENTRATED INDUSTRIAL FORMULATION

- PROVIDES A HIGH LUBRICITY FOAM SHIELD WHICH PREVENTS ADHESION OF ASPHALT TO TRUCK BEDS AND SIDES
- A STABLE, COMPLEX BLEND OF OILS, EMULSIFYING AGENTS AND HEAT RESISTANT RELEASE AGENTS

1 Gal. 5 Gal. 55 Gal. 275 Gal.

Inhalation: Remove affected person to fresh air; provide oxygen if breathing is difficult; if affected person is not breathing, administer CPR and seek emergency medical attention.

Skin: Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

Eyes: Check for and remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

Ingestion: DO NOT induce vomiting; if vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs; seek immediate medical attention. Vomiting may be induced only under the supervision of a physician.

TRANSPORT INFORMATION:

Proper Shipping Name - Not Regulated for Transport by Truck
 DOT Hazard Class - Not Regulated
 Packing Group - Not Regulated
 ID# - None

PowerKleen

Quality Chemicals • Superior Service

Power Kleen Corporation

To Reorder, Call: (813) 854-2648

FAX (813) 854-3133

In Case Of Chemical Emergency Contact

Chem-Tel 24 Hours (800) 255-3924

www.PowerKleen.com