

Directions:

- Mix 1 gallon of product with 35 gallons of water and apply as a thick foam through a foaming device.
- For the beds of trucks carrying asphalt, apply liberally to the truck bed.
- May be used in stronger concentrations if desired to increase residual effect.
- To prevent adhesion of mix to equipment or hand tools, apply the solution by spray or immersion. Will not affect asphalt or vehicles.

KEEP OUT OF REACH OF CHILDREN.
 DO NOT TAKE INTERNALLY.
 AVOID CONTACT WITH EYES.

Asphalt Release

SURFACE PROTECTANT

Industrial-grade soap concentrate

- **A CONCENTRATED BLEND OF BIODEGRADABLE SOAP AND DETERGENTS DESIGNED TO COAT ALL SURFACES THAT MAY COME IN CONTACT WITH ASPHALT**
- **FOR USE IN SETTING FREE ASPHALT WHICH MAY COME IN CONTACT WITH TRUCK BEDS**

1 Gal. 5 Gal. 55 Gal. 275 Gal.

Inhalation: None Expected. Remove affected person to fresh air; if symptoms persist seek medical attention.

Skin: None Expected. Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

Eyes: Check for and remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

Ingestion: Give two glasses of water for dilution; DO NOT induce vomiting; never give anything by mouth to an unconscious person; seek medical attention.

TRANSPORT INFORMATION:

Proper Shipping Name - Not Regulated for Transport by Truck
 DOT Hazard Class - Not Regulated
 Packing Group - Not Regulated
 ID# - None

PowerKleen

Quality Chemicals • Superior Service

Power Kleen Corporation

To Reorder, Call: (813) 854-2648

FAX (813) 854-3133

In Case Of Chemical Emergency Contact

Chem-Tel 24 Hours (800) 255-3924

www.PowerKleen.com