

PowerKleen
Quality Chemicals • Superior Service

Directions:

- Dilutions will vary from full strength to 1 oz. per gal. (1 to 128) depending on soil accumulation and the nature of the surface.
- Hot water will reduce cleaning time and improve performance.
- Released soil should be removed by rinsing with clean water or wiping with a clean cloth or sponge.
- Use less water or soak longer for heavily soiled surfaces.

Super Power X

INDUSTRIAL DEGREASER

INDUSTRIAL GRADE CONCENTRATED FORMULATION

- **APPLICABLE TO BOTH MANUAL AND PRESSURE WASHING EQUIPMENT**
- **THIS ALL PURPOSE CLEANER CAN BE USED ON ANY HARD SURFACE THAT IS NOT DAMAGED BY WATER**

KEEP OUT OF REACH OF CHILDREN.

DO NOT TAKE INTERNALLY. HARMFUL IF SWALLOWED.

AVOID CONTACT WITH EYES AND SKIN.

1 Gal. 5 Gal. 55 Gal. 275 Gal.



TRANSPORT INFORMATION:

Proper Shipping Name -
Corrosive Liquids, N.O.S.,
(Contains Sodium Hydroxide)
DOT Hazard Class - 8 Packing Group - III
ID# - UN 1760

Inhalation: Remove affected person to fresh air; wash mouth & nasal passages with water repeatedly. If breathing difficulty persists, seek medical attention.

Skin: Remove contaminated clothing; wash affected area with soap and water; if irritation persists, seek medical attention. DO NOT attempt to neutralize with chemical agents. Launder contaminated clothing before reuse.

Eyes: Remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; get medical attention immediately.

Ingestion: Drink large quantities of water or milk; give diluted vinegar or lemon juice to conscious person; DO NOT induce vomiting; seek medical attention.

PowerKleen

Quality Chemicals • Superior Service

Power Kleen Corporation

To Reorder, Call: (813) 854-2648

FAX (813) 854-3133

In Case Of Chemical Emergency Contact

Chem-Tel 24 Hours (800) 255-3924

www.PowerKleen.com