

NOVOC A-CL - Acid Replacement Technology

PATENTED — THE WORLD'S ONLY NON-ACID CONCRETE EQUIPMENT WASH

WHAT IS NOVOC A-CL?

NOVOC A-CL is a synthetic acid that is 100% Biodegradable, Non-Corrosive, Non-Regulated, and a Non-Skin Irritant. ART has been used in the Concrete Industry to replace the harsh acids used to dissolve concrete. These harsh acids have posed a threat to our health, our equipment, and our environment. Developed by Peach State Laboratories, Acid Replacement Technology (ART) is compliant with EPA, OSHA, and DOT regulations.

MANUFACTURING AND DISTRIBUTION OF NOVOC A-CL

Peach State Laboratories and their ART technology, now in partnership with Power Kleen Corporation, joins the Right Off Family of products. Currently the largest manufacturer of concrete products in the United States, Power Kleen cements **NOVOC A-CL**'s future in the industry as the sole manufacturer and distributor of Peach State's ART technology in the United States and abroad. **NOVOC A-CL** users will now enjoy the same unmatched research and development, service, technological advances, and product quality that Power Kleen customers have known for over 30 years.

NOVOC A-CL USE

NOVOC A-CL can be used as a daily truck wash to remove built-up concrete without any neutralization. **NOVOC A-CL** is so safe, it can be used on any surface, including glass, aluminum, chrome, rubber, plastic, or paint. **NOVOC A-CL** also includes detergents for degreasing, corrosion inhibitors, optical brighteners, foaming agents, water softeners, and surface expanders.

Start formulating with NOVOC A-CL today and enjoy the benefits of using a true, "one of a kind" concrete remover. Your customers, your equipment, and your employees will thank you!

PRODUCT HIGHLIGHTS:

- 100% Synthetic Acid
- Approved & Certified by Peach State Laboratories
- OSHA Compliant
- DOT Classification: Not Regulated
- Low Contributor To BOD/COD in Effluents
- A low pH Organic Salt that is used to replace traditional harsh acids
- No Phosphates
- Non-Fuming
- Safe on All Surfaces
- Safe on Skin
- Removes Concrete Quickly and Efficiently
- Removes Grease and Grime
- Up to 10 times more effective than other industry products when dissolving Calcium Carbonate

TRANSPORT INFORMATION:

Proper Shipping Name -
Non-Hazardous for Transport by Truck
DOT Hazard Class - Not Regulated
Packing Group - Not Regulated
ID# - None

AVAILABLE IN:

1 Gal Jug, 5 Gal Bucket, 55 Gal Drum,
275 Gal Tote, 300 Gal Leg Tank
or delivered via Tanker Truck



GUARANTEE:

Jamson Labs' / Power Kleen's manufacturing and laboratory controls ensure uniform quality throughout our product line. All Jamson Labs / Power Kleen manufactured products are guaranteed for 1 year when used as directed.

NOVOC A-CL - Acid Replacement Technology

PRODUCT #: PK-9260

PRODUCT STUDIES

Metal Studies

Department of Transportation (DOT) Shipping Test Protocols as per Section 173.154 Exceptions for Class 8 (corrosive materials): A liquid is considered to be corrosive if its corrosion rate exceeds 6.25 mmpy on Steel (SAE 1020 carbon steel) at a test temperature of 55° C.

Results of NOVOC A-CL Testing: SAE 1020 carbon steel = 0.64 mmpy

Conclusion: NOVOC A-CL was proven to be a Non-Regulated material with regards to shipping over the road.

Toxicity Studies

Test Procedure OECD 202, 48hour

Results of NOVOC A-CL Testing: LC 50 and LD 50 (rat oral) scores found RMWW to be Non-Toxic.

Dermal Irritation Study

A modified Draize method was used as described in OECD Guidelines for the Testing of Chemicals, Sec. 404, Paris 1981 (revised 1992). This study complies with the requirements of OECD Principles of GLP, Annex, Paris, 1981, revised as of July 1992.

Results of NOVOC A-CL Testing: NOVOC A-CL received a Primary Irritation Score of 2.1 ± 0.9 and is classified as a Non-Skin Irritant.

Mutagenicity Studies

Tested by the Ames Assay (OCED Guidelines for Testing of Chemicals, Sec. 471).

Results of NOVOC A-CL Testing: NOVOC A-CL was found

NOT TO BE MUTAGENIC.

Biodegradation & Aquatic

Safety

Test Procedure: Hach Reactor Digestion method for Waste Water and Sea Water. Hach Reactor Digestion Method is a semi-micro adaptation of the Standard Methods.

Results of NOVOC A-CL Testing: NOVOC A-CL was found to be 100% Biodegradable.

COD = Low Detectable Limits
BOD = No Detectable Limits

CLASSIFICATIONS & APPROVALS

NON-Regulated

DOT, TDG, IMO, IATA, IMDG, SARA 313 311-312, California Prop 65

FDA

Approved as Safe (GRAS)

USDA Authorization

A1, A2, A3, A4, A7, A8, C2, G6 & G7

RESEARCH & DEVELOPMENT

Power Kleen Corporation maintains a fully equipped laboratory and a chemist on hand at all times. We not only maintain the superior level of

quality set for our products but continually strive to develop cleaning solutions for the future.

PRODUCT QUALITY

NOVOC A-CL is strictly monitored by both Peach State Laboratories & Power Kleen Corporation. Each batch of NOVOC A-CL produced is checked for quality by Peach State and then again by Power Kleen before packaging. Random samples are also taken from the field every month and are tested again by both companies. Products are checked for quality, contamination, and tampering.

TECHNICAL DATA

Phosphoric Acid: None
 Muriatic Acid: None
 Hydrochloric Acid: None
 Sulfuric Acid: None
 Hydrofluoric Acid: None
 Nitrate Level: None
 Rinse Additives: Positive
 Detergent Package: Positive
 Surfactant Package: Positive
 Solvent Package: Positive
 Emulsifiers: Positive
 Shipper Regulations: None
 Weight: 9.09
 Odor: Mild
 Characteristic

