



Danger

• Hazard-determining components of labeling:

Mineral Acid Salt of Organic Amide

• Hazard statements

Harmful if swallowed.

Causes skin irritation.

Causes serious eye irritation.

• Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P280 Wear protective gloves / eye protection / face protection.

P301+P312 If swallowed: Call a poison center/doctor if you feel unwell.

P330 Rinse mouth.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present

and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with

local/regional/national/international

regulations.

TORNADO

ACID REPLACEMENT TECHNOLOGY

INDUSTRIAL-GRADE FORMULATION

- **100% BIODEGRADABLE, NON-CORROSIVE, NON-REGULATED, AND A NON-SKIN IRRITANT**

- Low pH organic salt used to replace traditional mineral & organic acids
- 71% the strength of hydrochloric acid when dissolving calcium carbonate
- 4 To 10 Times more effective than Citric and Glycolic Acid and 2 to 3 times more effective than Phosphoric Acid when dissolving Calcium Carbonate
- Performance & cost advantages verses acids such as Phosphoric, Citric, Glycolic, Sulfamic, Oxalic, Etc.
- DOT Classification: Non-Regulated
- Non-fuming
- No solubility limits (perfect fit in concentrated cleaners)
- Classified as a mild skin irritant
- Replaces multiple acid blends
- Phosphate free & contains no VOCs
- Low contributor to BOD/COD in effluents

TRANSPORT INFORMATION:

Proper Shipping Name - Non-Hazardous for Transport by truck

DOT Hazard Class - Not Regulated

Packing Group - Not Regulated

ID# - None

D.O.T. NON-REGULATED

PowerKleen

Quality Chemicals • Superior Service

101 S. Bayview Blvd. Oldsmar, FL 34677

To Reorder, Call: (813) 854-2648

FAX (813) 854-3133

In Case Of Chemical Emergency Contact

Chem-Tel 24 Hours (800) 255-3924

www.PowerKleen.com

1 Gal.

5 Gal.

55 Gal.

275 Gal.