

**PowerKleen**  
Quality Chemicals • Superior Service

**Directions:**

- Mix 1 gallon of product with 10 gallons of water.
- For the beds of trucks carrying asphalt, apply liberally to the truck bed.
- May be used in stronger concentrations if desired to increase residual effect.
- To prevent adhesion of mix to equipment or hand tools, apply the solution by spray or immersion. Will not affect asphalt or vehicles.

# 307622

**ASPHALT RELEASE AGENT**

- **FOR USE IN SETTING FREE ASPHALT WHICH MAY COME IN CONTACT WITH TRUCK BEDS**

**KEEP OUT OF REACH OF CHILDREN.  
DO NOT TAKE INTERNALLY.  
AVOID CONTACT WITH EYES.**

1 Gal.

5 Gal.

55 Gal.

275 Gal.

**Inhalation:** None Expected. Remove affected person to fresh air; if symptoms persist seek medical attention.

**Skin:** None Expected. Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

**Eyes:** Check for and remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

**Ingestion:** Give two glasses of water for dilution; DO NOT induce vomiting; never give anything by mouth to an unconscious person; seek medical attention.

**TRANSPORT INFORMATION:**

Proper Shipping Name - Not Regulated for Transport by Truck  
DOT Hazard Class - Not Regulated  
Packing Group - Not Regulated  
ID# - None

**PowerKleen**  
Quality Chemicals • Superior Service

Power Kleen Corporation  
To Reorder, Call: (813) 854-2648  
FAX (813) 854-3133

In Case Of Chemical Emergency Contact  
Chem-Tel 24 Hours (800) 255-3924  
[www.PowerKleen.com](http://www.PowerKleen.com)