

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2014

Reviewed on 03/21/2014

1 Identification

- **Product identifier**
- **Trade name:** Lacquer Thinner 210
- **Article number:** 0210 JLM
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Jamson Laboratories, Inc.
101 South Bayview Blvd.
Oldsmar, FL 34677
USA
- **Information department:** Product Safety Department
- **Emergency telephone number:** ChemTel Inc. (800) 255-3924 Intl. +01 (813) 248-0585



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

toluene

Solvent naphtha (petroleum), light aliph.

(Contd. on page 2)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2014

Reviewed on 03/21/2014

Trade name: Lacquer Thinner 210

(Contd. of page 1)

- **Hazard statements**

Highly flammable liquid and vapor.
 Causes skin irritation.
 Causes serious eye irritation.
 Suspected of damaging fertility or the unborn child.
 May cause drowsiness or dizziness.
 May cause damage to organs through prolonged or repeated exposure.
 May be fatal if swallowed and enters airways.

- **Precautionary statements**

If medical advice is needed, have product container or label at hand.
 Keep out of reach of children.
 Read label before use.
 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

67-64-1	acetone	25-50%
108-88-3	toluene	25-50%
64742-89-8	Solvent naphtha (petroleum), light aliph.	10-25%
67-63-0	propan-2-ol	10-25%
1330-20-7	xylene (mix)	2.5-10%
78-93-3	butanone	≤ 2.5%
108-10-1	4-methylpentan-2-one	≤ 2.5%
100-41-4	ethylbenzene	≤ 2.5%

USA

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2014

Reviewed on 03/21/2014

Trade name: *Lacquer Thinner 210*

(Contd. of page 2)

4 First-aid measures

- **Description of first aid measures**

- **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:**

Remove contact lenses if able to do so.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:**

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed**

Nausea

Coughing

Unconsciousness

Gastric or intestinal disorders

Dizziness

Headache

- **Danger**

Danger of pulmonary edema.

Danger of impaired breathing.

Danger of disturbed cardiac rhythm.

- **Indication of any immediate medical attention and special treatment needed**

Medical supervision for at least 48 hours.

If swallowed or in case of vomiting, danger of entering the lungs.

5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **Special hazards arising from the substance or mixture** No further relevant information available.

- **Advice for firefighters**

- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:**

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2014

Reviewed on 03/21/2014

Trade name: Lacquer Thinner 210

(Contd. of page 3)

See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:**
Store away from oxidizing agents.
Store away from foodstuffs.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

67-64-1 acetone

PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: (1782) NIC-1187 mg/m ³ , (750) NIC-500 ppm
	Long-term value: (1188) NIC-475 mg/m ³ , (500) NIC-200 ppm
	BEI

108-88-3 toluene

PEL	Long-term value: 200 ppm
	Ceiling limit value: 300; 500* ppm
	*10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm
	Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 75 mg/m ³ , 20 ppm
	BEI

67-63-0 propan-2-ol

PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm
	Long-term value: 980 mg/m ³ , 400 ppm

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2014

Reviewed on 03/21/2014

Trade name: **Lacquer Thinner 210**

(Contd. of page 4)

<i>TLV</i>	<i>Short-term value: 984 mg/m³, 400 ppm</i> <i>Long-term value: 492 mg/m³, 200 ppm</i> <i>BEI</i>
------------	---

1330-20-7 xylene (mix)

<i>PEL</i>	<i>Long-term value: 435 mg/m³, 100 ppm</i>
<i>REL</i>	<i>Short-term value: 655 mg/m³, 150 ppm</i> <i>Long-term value: 435 mg/m³, 100 ppm</i>
<i>TLV</i>	<i>Short-term value: 651 mg/m³, 150 ppm</i> <i>Long-term value: 434 mg/m³, 100 ppm</i> <i>BEI</i>

78-93-3 butanone

<i>PEL</i>	<i>Long-term value: 590 mg/m³, 200 ppm</i>
<i>REL</i>	<i>Short-term value: 885 mg/m³, 300 ppm</i> <i>Long-term value: 590 mg/m³, 200 ppm</i>
<i>TLV</i>	<i>Short-term value: 885 mg/m³, 300 ppm</i> <i>Long-term value: 590 mg/m³, 200 ppm</i> <i>BEI</i>

108-10-1 4-methylpentan-2-one

<i>PEL</i>	<i>Long-term value: 410 mg/m³, 100 ppm</i>
<i>REL</i>	<i>Short-term value: 300 mg/m³, 75 ppm</i> <i>Long-term value: 205 mg/m³, 50 ppm</i>
<i>TLV</i>	<i>Short-term value: 307 mg/m³, 75 ppm</i> <i>Long-term value: 82 mg/m³, 20 ppm</i> <i>BEI</i>

100-41-4 ethylbenzene

<i>PEL</i>	<i>Long-term value: 435 mg/m³, 100 ppm</i>
<i>REL</i>	<i>Short-term value: 545 mg/m³, 125 ppm</i> <i>Long-term value: 435 mg/m³, 100 ppm</i>
<i>TLV</i>	<i>Short-term value: 543 mg/m³, 125 ppm</i> <i>Long-term value: 87 mg/m³, 20 ppm</i> <i>BEI</i>

· Ingredients with biological limit values:**67-64-1 acetone**

<i>BEI</i>	<i>50 mg/L</i> <i>Medium: urine</i> <i>Time: end of shift</i> <i>Parameter: Acetone (nonspecific)</i>
------------	--

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2014

Reviewed on 03/21/2014

Trade name: Lacquer Thinner 210

(Contd. of page 5)

108-88-3 toluene

BEI 0.02 mg/L
 Medium: blood
 Time: prior to last shift of workweek
 Parameter: Toluene

0.03 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Toluene

0.3 mg/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: o-Cresol with hydrolysis (background)

67-63-0 propan-2-ol

BEI 40 mg/L
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: Acetone (background, nonspecific)

1330-20-7 xylene (mix)

BEI 1.5 g/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: Methylhippuric acids

78-93-3 butanone

BEI 2 mg/L
 Medium: urine
 Time: end of shift
 Parameter: MEK

108-10-1 4-methylpentan-2-one

BEI 1 mg/L
 Medium: urine
 Time: end of shift
 Parameter: MIBK

100-41-4 ethylbenzene

BEI 0.7 g/g creatinine
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-
 Medium: end-exhaled air
 Time: not critical
 Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2014

Reviewed on 03/21/2014

Trade name: **Lacquer Thinner 210**

(Contd. of page 6)

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Neoprene gloves

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Not suitable are gloves made of the following materials:**

Natural rubber, NR

Strong gloves

Leather gloves

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Solvent resistant protective clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Liquid
Color:	Clear
Odor:	Solvent-like
Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55 °C (131 °F)

· **Flash point:** -19 °C (-2 °F)

· **Flammability (solid, gaseous):** Not applicable.

(Contd. on page 8)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2014

Reviewed on 03/21/2014

Trade name: *Lacquer Thinner 210*

(Contd. of page 7)

· Ignition temperature:	425 °C (797 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	13.0 Vol %
· Vapor pressure at 20 °C (68 °F):	233 hPa (175 mm Hg)
· Density at 20 °C (68 °F):	0.802 g/cm ³ (6.693 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	100.0 %
VOC content:	73.0 %
	585.5 g/l / 4.89 lb/gl
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions**
 - Reacts with oxidizing agents.
 - Reacts with oxygen.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
 - Carbon monoxide and carbon dioxide
 - Hydrocarbons

USA

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2014

Reviewed on 03/21/2014

Trade name: **Lacquer Thinner 210**

(Contd. of page 8)

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

108-88-3 toluene		
Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)
1330-20-7 xylene (mix)		
Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** Irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
67-63-0	propan-2-ol	3
1330-20-7	xylene (mix)	3
100-41-4	ethylbenzene	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

USA

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2014

Reviewed on 03/21/2014



Trade name: Lacquer Thinner 210

(Contd. of page 9)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

<ul style="list-style-type: none"> · UN-Number · DOT, IMDG, IATA 	UN1263
<ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG, IATA 	Paint related material PAINT RELATED MATERIAL
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT 	<div style="text-align: center;">  <p>3</p> </div>
<ul style="list-style-type: none"> · Class · Label 	3 Flammable liquids. 3
<ul style="list-style-type: none"> · IMDG, IATA 	<div style="text-align: center;">  <p>3</p> </div>
<ul style="list-style-type: none"> · Class · Label 	3 Flammable liquids. 3
<ul style="list-style-type: none"> · Packing group · DOT, IMDG, IATA 	II
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: 	No
<ul style="list-style-type: none"> · Special precautions for user · Danger code (Kemler): · EMS Number: 	33 F-E,S-E
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	Not applicable.
<ul style="list-style-type: none"> · UN "Model Regulation": 	UN1263, Paint related material, 3, II

USA

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2014

Reviewed on 03/21/2014

Trade name: **Lacquer Thinner 210**

(Contd. of page 10)

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

108-88-3	toluene
67-63-0	propan-2-ol
1330-20-7	xylene (mix)
78-93-3	butanone
108-10-1	4-methylpentan-2-one
100-41-4	ethylbenzene

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

108-10-1	4-methylpentan-2-one
100-41-4	ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

108-88-3	toluene
----------	---------

· **Chemicals known to cause reproductive toxicity for males.**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
----------	---------

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
108-88-3	toluene	II
1330-20-7	xylene (mix)	I
78-93-3	butanone	I
108-10-1	4-methylpentan-2-one	I
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1	acetone	A4
108-88-3	toluene	A4
67-63-0	propan-2-ol	A4
1330-20-7	xylene (mix)	A4
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

Substance is listed as a suspected carcinogen.

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2014

Reviewed on 03/21/2014

Trade name: **Lacquer Thinner 210**

(Contd. of page 11)

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

toluene

Solvent naphtha (petroleum), light aliph.

· **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· **Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing MSDS:** Environment protection department.

· **Date of preparation / last revision** 5/23/2014 Revisions to section 14 "Transport."

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent