

DILUTION	PARTS CLEANER	PARTS WATER
A	1	75
B	1	40
C	1	20
D	1	15
E	1	5
F	1	5
G	1	3

Directions: This all purpose cleaner can be used on any hard surface that is not damaged by water. It is applicable to both manual and pressure washing equipment. Dilutions will vary from full strength to 1 oz. per gal 1 to 128 depending on soil accumulation and the nature of the surface. Hot water will reduce cleaning time and improve performance. Released soil should be removed by rinsing with clean water or wiping with a clean cloth or sponge. Suggested dilutions are for average soil loads. use less water or soak longer for heavily soiled surfaces.

AUTOMOTIVE USES:

Degreasing Engines: Spray on H. Soak 3-5 minutes. Scrub with a stiff brush & rinse.

Vinyl Tops: Wash with D. Rinse.

White Wall Tires: Spray on G. and soak. Scrub with a stiff brush. Rinse.

SCHOOLS:

Lockers, File Cabinets: Wash with C. Rinse and wipe clean.

Showers, Swimming Pool Decks: Wash with G. Rinse thoroughly.

KITCHENS:

Ovens, Canopies, Fryers: Wash with G.

Wipe or rinse thoroughly.

Painted Walls: Wash with B. Rinse or wipe thoroughly.

Refrigerators, Freezers: Wash with E. Rinse or wipe throughly.

Lighting Fixtures: Wash with D. Rinse or wipe well.

WALLS:

Painted Surfaces: Wash with B. Wipe Clean.

Mildew & Fungus: Wash with C. Rinse or wipe thoroughly.

FLOORS: **Maintenance:** Mop with B. Rinse and take up water.

Wax Stripping: Spread on E. Soak 10 minutes. Remove released wax with clean water, taking up with a wet vacuum or clean mop.

Stripping Metal Interlock Finishes: Add 1 cup household ammonia per gallon of E. Mop on and soak for 15 minutes. Brush vigorously.

Rinse with warm water and take up with a wet vacuum or clean mop.

MACHINERY & EQUIPMENT

Printing Presses, Spray Rigs, Mining

Equipment: Spray on D. Soak 10 minutes. Rinse or wipe clean.

PowerKleen
Quality Chemicals • Superior Service

PK-600

All-Purpose Cleaner

MULTI-PURPOSE CLEANER & DEGREASER

COMMERCIAL-GRADE CONCENTRATE FORMULATION

• SAFELY CLEANS AND DEGREASES

REMOVES: • WAXES • GREASE • CARBONS • SOOT
• GUMS • RESINS • OILS • DYES • SCUM • INKS

• USE IN CONJUNCTION WITH RECLAIM SYSTEMS
TO HELP SEPARATE OILS FROM YOUR WASH WATER

1 Gal.

5 Gal.

55 Gal.

275 Gal.



TRANSPORT INFORMATION:

Proper Shipping Name -
Corrosive Liquids, N.O.S.,
(Contains Sodium Metasilicate)
DOT Hazard Class - 8 Packing Group - II
ID# - UN 1760

Inhalation: Remove affected person to fresh air; wash mouth and nasal passages with water repeatedly; if breathing difficulties persist seek medical attention.

Skin: Remove contaminated clothing; wash affected area with soap and water; DO NOT attempt to neutralize with chemical agents; if irritation persists, seek medical attention. Launder contaminated clothing before reuse.

Eyes: Check for and remove any contact lenses. Immediately flush eyes with clear running water for 15 minutes while holding eyelids open. Seek medical attention immediately.

Ingestion: Drink two glasses of water or milk; give diluted vinegar or lemon juice to conscious person; DO NOT induce vomiting; seek medical attention immediately.

PowerKleen

Quality Chemicals • Superior Service

Power Kleen Corporation

To Reorder, Call: (813) 854-2648

FAX (813) 854-3133

In Case Of Chemical Emergency Contact

Chem-Tel 24 Hours (800) 255-3924

www.PowerKleen.com

DANGER:

DO NOT TAKE INTERNALLY. HARMFUL IF SWALLOWED.

AVOID CONTACT WITH EYES AND SKIN

CAUTION: KEEP OUT OF REACH OF CHILDREN.