

Cleaner & Wax Stripper- All-Purpose, Ammoniated

PRODUCT #: PK-0601

CHARACTERISTICS:

Appearance: Blue liquid
 Odor: Ammonia
 pH: 12.90
 Specific Gravity: 1.000
 Weight: 8.34
 Viscosity: Water Like
 Flash Point: N/A
 Dilution: 1:30

TRANSPORT INFO:

Proper Shipping Name - Corrosive Liquids, N.O.S.,
 (Contains Sodium Metasilicate)
 DOT Hazard Class - 8
 Packing Group - II
 ID# - UN 1760

DILUTION	PARTS CLEANER	PARTS WATER
A	1	75
B	1	40
C	1	20
D	1	15
E	1	5
F	1	5
G	1	3



ADVANTAGES:

Professional-grade concentrated formulation removes: waxes, grease, carbons, soot Gums, resins, oils, dyes, scum and inks.

DIRECTIONS:

This all purpose cleaner can be used on any hard surface that is not damaged by water. It is applicable to both manual and pressure washing equipment. Dilutions will vary from full strength to 1 oz. Per gallon 1 to 128 depending on soil accumulation and the nature of the surface. Hot water will reduce cleaning time and improve performance. Released soil should be removed by rinsing with clean water or wiping with a clean cloth or sponge. Suggested dilutions are for average soil loads, use less water or soak longer for heavily soiled surfaces.

Use dilution table above as per the following instructions:

AUTOMOTIVE- Degreasing Engines: Spray on G. Soak 3-5 minutes. Scrub with a stiff brush. Rinse. **Vinyl Tops:** Wash with D. Rinse. **White Wall Tires:** Spray on G. and soak. Scrub with a stiff brush. Rinse.

SCHOOLS- Lockers, File Cabinets: Wash with C. Rinse and wipe clean. **Showers, Swimming Pool Decks:** Wash with G. Rinse thoroughly.

KITCHENS- Ovens, Fryers: Wash with G. Wipe or rinse thoroughly. **Painted Walls:** Wash with B. Rinse or wipe thoroughly. **Refrigerators, Freezers:** Wash with E. Rinse or wipe thoroughly. **Lighting Fixtures:** Wash with D. Rinse or wipe well.

WALLS- Painted Surfaces: Wash with B. Wipe Clean. **Mildew & Fungus:** Wash with C. Rinse or wipe thoroughly.

FLOORS- Maintenance: Mop with B. Rinse and take up water. **Wax Stripping:** Spread on E. Soak 10 minutes. Remove released wax with clean water, taking up with a wet vacuum or clean mop. **Stripping Metal Interlocked Finishes:** Add 1 cup of household ammonia per gallon of E. Mop on and soak for 15 minutes. Brush vigorously. Rinse with warm water and take up with a wet vacuum or clean mop.

MACHINERY AND EQUIPMENT- Printing Presses, Mill Machinery, Spray Rigs, Earth Movers, Mining Equipment: Spray on D. Soak 10 minutes. Rinse or wipe clean.

PRECAUTIONS:

Inhalation: Remove affected person to fresh air; wash mouth and nasal passages with water repeatedly; if breathing difficulties persist seek medical attention.

Skin: Remove contaminated clothing; wash affected area with soap and water; DO NOT attempt to neutralize with chemical agents; if irritation persists, seek medical attention. Launder contaminated clothing before reuse.

Eyes: Check for and remove any contact lenses. Immediately flush eyes with clear running water for 15 minutes while holding eyelids open. Seek medical attention immediately.

GUARANTEE: Jamson Labs' / Power Kleen's manufacturing and laboratory controls ensure uniform quality throughout our product line. All Jamson Labs / Power Kleen manufactured products are guaranteed for 1 year when used as directed.

Ingestion: Drink two glasses of water or milk; give diluted vinegar or lemon juice to conscious person; DO NOT induce vomiting; seek medical attention immediately.



AVAILABLE IN:

Gal. Jug, 5 Gal. Bucket, 55 Gal. Drum, 275 Gal. Tote, 300 Gal. Leg Tank or delivered via Tanker Truck

