

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2015

Reviewed on 03/17/2015

1 Identification

- **Product identifier**
- **Trade name:** Ammoniated Wax Stripper
- **Article number:** PK 0601
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Power Kleen Corporation
101 South Bayview Blvd.
OLDSMAR, FL 34677
USA
- **Information department:** Product Safety Department
- **Emergency telephone number:** ChemTel Inc. (800) 255-3924 Intl. +01 (813) 248-0585



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05

- **Signal word** Danger
- **Hazard-determining components of labeling:**
disodium metasilicate
- **Hazard statements**
Causes severe skin burns and eye damage.
- **Precautionary statements**
If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read label before use.
Do not breathe dusts or mists.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center/doctor.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2015

Reviewed on 03/17/2015

Trade name: Ammoniated Wax Stripper

(Contd. of page 1)

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

6834-92-0	disodium metasilicate	2.5-10%
66455-15-0	C10-12 6 Mole Linear Alcohol Ethoxylate	≤ 2.5%
111-76-2	2-butoxyethanol	≤ 2.5%
67-63-0	propan-2-ol	≤ 2.5%
1310-73-2	sodium hydroxide	≤ 2.5%
1336-21-6	ammonia, aqueous solution	≤ 2.5%

4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:**

Remove contact lenses if able to do so.

Rinse opened eye for several minutes under running water. Then consult a doctor.

- **After swallowing:**

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

- **Most important symptoms and effects, both acute and delayed**

Cramp

Nausea

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2015

Reviewed on 03/17/2015

Trade name: Ammoniated Wax Stripper

(Contd. of page 2)

- Gastric or intestinal disorders
- **Danger** Danger of gastric perforation.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Unsuitable material for receptacle: glass or ceramic.
Unsuitable material for receptacle: aluminium.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2015

Reviewed on 03/17/2015

Trade name: Ammoniated Wax Stripper

(Contd. of page 3)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

111-76-2 2-butoxyethanol

PEL	Long-term value: 240 mg/m ³ , 50 ppm Skin
REL	Long-term value: 24 mg/m ³ , 5 ppm Skin
TLV	Long-term value: 97 mg/m ³ , 20 ppm BEI

67-63-0 propan-2-ol

PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm BEI

1310-73-2 sodium hydroxide

PEL	Long-term value: 2 mg/m ³
REL	Ceiling limit value: 2 mg/m ³
TLV	Ceiling limit value: 2 mg/m ³

· **Ingredients with biological limit values:**

111-76-2 2-butoxyethanol

BEI	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis
-----	--

67-63-0 propan-2-ol

BEI	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----	---

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2015

Reviewed on 03/17/2015

Trade name: Ammoniated Wax Stripper

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Neoprene gloves

Butyl rubber, BR

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Not suitable are gloves made of the following materials:** Leather gloves

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Alkaline resistant protective clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Blue

· **Odor:** Ammonia-like

· **Odour threshold:** Not determined.

· **pH-value at 20 °C (68 °F):** 12.9

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 100 °C (212 °F)

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:**

Decomposition temperature: Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

Lower: Not determined.

Upper: Not determined.

· **Vapor pressure:** Not determined.

· **Density at 20 °C (68 °F):** 1 g/cm³ (8.345 lbs/gal)

· **Relative density** Not determined.

· **Vapour density** Not determined.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2015

Reviewed on 03/17/2015

Trade name: Ammoniated Wax Stripper

(Contd. of page 5)

· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	3.1 %
Water:	87.3 %
VOC content:	5.7 %
	31.4 g/l / 0.26 lb/gl
Solids content:	7.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Reacts with strong acids and oxidizing agents.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
 - Sodium Oxides
 - Nitrogen oxides
 - Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
 - **on the skin:** Strong caustic effect on skin and mucous membranes.
 - **on the eye:**
 - Strong caustic effect.
 - Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
 - The product shows the following dangers according to internally approved calculation methods for preparations:
 - Harmful
 - Corrosive
 - Irritant
 - Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2015

Reviewed on 03/17/2015

Trade name: Ammoniated Wax Stripper

(Contd. of page 6)

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer)**

111-76-2	2-butoxyethanol	3
67-63-0	propan-2-ol	3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

· **Additional ecological information:**· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· **UN-Number**· **DOT, IMDG, IATA**

UN3266

· **UN proper shipping name**· **DOT**

Corrosive liquid, basic, inorganic, n.o.s. (Sodium hydroxide, Disodium trioxosilicate)

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2015

Reviewed on 03/17/2015

Trade name: Ammoniated Wax Stripper

(Contd. of page 7)

· **IMDG, IATA** *CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (SODIUM HYDROXIDE, DISODIUM TRIOXOSILICATE)*

· **Transport hazard class(es)**· **DOT**· **Class** 8 Corrosive substances· **Label** 8· **IMDG, IATA**· **Class** 8 Corrosive substances· **Label** 8· **Packing group**· **DOT, IMDG, IATA** III· **Environmental hazards:**· **Marine pollutant:** No· **Special precautions for user**· **Danger code (Kemler):** 80· **EMS Number:** F-A,S-B· **Segregation groups** Alkalis· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.· **Transport/Additional information:**· **DOT**· **Quantity limitations** On passenger aircraft/rail: 5 LOn cargo aircraft only: 60 L· **IMDG**· **Limited quantities (LQ)** 5L· **Excepted quantities (EQ)** Code: E1Maximum net quantity per inner packaging: 30 mlMaximum net quantity per outer packaging: 1000 ml· **UN "Model Regulation":** *UN3266, Corrosive liquid, basic, inorganic, n.o.s. (Sodium hydroxide, Disodium trioxosilicate), 8, III*

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2015

Reviewed on 03/17/2015

Trade name: Ammoniated Wax Stripper

(Contd. of page 8)

· Section 313 (Specific toxic chemical listings):

111-76-2	2-butoxyethanol
67-63-0	propan-2-ol
7758-29-4	pentasodium triphosphate
1336-21-6	ammonia, aqueous solution
67-56-1	methanol

· TSCA (Toxic Substances Control Act):

6834-92-0	disodium metasilicate
66455-15-0	C10-12 6 Mole Linear Alcohol Ethoxylate
111-76-2	2-butoxyethanol
67-63-0	propan-2-ol
7758-29-4	pentasodium triphosphate
1310-73-2	sodium hydroxide
68604-71-7	Disodium cocoamphodipropionate
1336-21-6	ammonia, aqueous solution
64-02-8	tetrasodium ethylenediaminetetraacetate
67-56-1	methanol
7732-18-5	water, distilled, conductivity or of similar purity

· Proposition 65
· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

67-56-1 | methanol

· Carcinogenic categories
· EPA (Environmental Protection Agency)

111-76-2	2-butoxyethanol	NL
----------	-----------------	----

· TLV (Threshold Limit Value established by ACGIH)

111-76-2	2-butoxyethanol	A3
67-63-0	propan-2-ol	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms


GHS05

· Signal word Danger

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2015

Reviewed on 03/17/2015

Trade name: Ammoniated Wax Stripper

(Contd. of page 9)

· **Hazard-determining components of labeling:**

disodium metasilicate

· **Hazard statements**

Causes severe skin burns and eye damage.

· **Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Do not breathe dusts or mists.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Date of preparation / last revision** 03/17/2015 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1