Printing date 12/30/2014

Reviewed on 03/19/2014

1 Identification	
· Product identifier	
· Trade name: <u>Tire Lubricant</u>	Jamson Labs Power Kleen
• Article number: 0068 PK	Chemical Solutions Since 1973
• Details of the supplier of the safety data sheet • Manufacturer/Supplier: Power Kleen Corporation 101 South Bayview Blvd. OLDSMAR, FL 34677 USA	Chemical Solutions Since 1975
• Information department: Product Safety Departme • Emergency telephone number: ChemTel Inc. (800)	
2 Hazard(s) identification	
· Classification of the substance or mixture	
GHS07	
Eye Irrit. 2A H319 Causes serious eye irritation.	
 Label elements GHS label elements The product is classified and laterated pictograms 	abeled according to the Globally Harmonized System (GHS).
GHS07	
· Signal word Warning	
 Hazard-determining components of labeling: Sodium Dodecyl Benzene Sulfonate Hazard statements Causes serious eye irritation. Precautionary statements If medical advice is needed, have product container Keep out of reach of children. Read label before use. Wear protective gloves/protective clothing/eye prote Wash thoroughly after handling. IF IN EYES: Rinse cautiously with water for sever Continue rinsing. If eye irritation persists: Get medical advice/attentio Classification system: NFPA ratings (scale 0 - 4) Health = 1 Fire = 0 Reactivity = 0 	ection/face protection. al minutes. Remove contact lenses, if present and easy to do.
	(Contd. on page 2)
	(Contra on page 2) USA

Printing date 12/30/2014

Reviewed on 03/19/2014

(Contd. of page 1)

Trade name: Tire Lubricant

· HMIS-ratings (scale 0 - 4)



• Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

68081-81-2 Sodium Dodecyl Benzene Sulfonate	2.5-10%
66455-15-0 C10-12 6 Mole Linear Alcohol Ethoxylate	<i>≤</i> 2.5%
Fragrance (Generic)	<i>≤</i> 2.5%

4 First-aid measures

· Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact:
- Remove contact lenses if able to do so.
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing:

Rinse out mouth and then drink plenty of water.

A person vomiting while lying on their back should be turned onto their side.

· Most important symptoms and effects, both acute and delayed

Gastric or intestinal disorders

Allergic reactions

Nausea

Cramp

· Indication of any immediate medical attention and special treatment needed

Medical supervision for at least 48 hours.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • Special hazards arising from the substance or mixture No further relevant information available.

- · Advice for firefighters
- · Protective equipment: No special measures required.

(Contd. on page 3)

US4

Printing date 12/30/2014

Reviewed on 03/19/2014

Trade name: Tire Lubricant

(Contd. of page 2)

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Dilute with plenty of water.
- Do not allow to enter sewers/ surface or ground water. • Methods and material for containment and cleaning up: Absorb with liquid binding material (and diatomite acid binders universal bin
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- *Reference to other sections* See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Store away from oxidizing agents. Store away from foodstuffs.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:
- The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.
- · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands: Not required.

(Contd. on page 4)

⁻ USA

Printing date 12/30/2014

Reviewed on 03/19/2014

Trade name: Tire Lubricant

• **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye protection:** Goggles recommended during refilling. Safety glasses

9 Physical and chemical properties

 Information on basic physical and General Information 	cnemicai properties	
· General Information · Appearance:		
Form:	Liquid	
Color:	Amber colored	
· Odor:	Coconut	
· Odour threshold:	Not determined.	
· pH-value at 20 °C (68 °F):	9	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	300 °C (572 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure:	Not determined.	
· Density at 20 °C (68 °F):	1.04 g/cm ³ (8.679 lbs/gal)	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octanol/wat	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	0.0~%	
Water:	91.2 %	
VOC content:	5.4 g/l / 0.04 lb/gl	
		(Contd. on page

(Contd. of page 3)

Printing date 12/30/2014

Reviewed on 03/19/2014

(Contd. of page 4)

Trade name: Tire Lubricant

Solids content: • Other information 19.5 % No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions
- Reacts with strong acids.
- Reacts with strong oxidizing agents.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- Hazardous decomposition products: Carbon monoxide and carbon dioxide Sulfur oxides (SOx) Nitrogen oxides

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: Irritating effect.
- Sensitization: Sensitizing effect by skin contact is possible with prolonged exposure.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

1

- · Aquatic toxicity: No further relevant information available.
- $\cdot \textit{Persistence and degradability} \textit{ No further relevant information available}.$
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

(Contd. on page 6)

USA ·

Printing date 12/30/2014

Reviewed on 03/19/2014

Trade name: Tire Lubricant

Danger to drinking water if even extremely small quantities leak into the ground.

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• vPvB: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

• Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number		
DOT	Not regulated	
UN proper shipping name		
DOT	Not regulated	
IMDG, IATA	Not applicable	
Transport hazard class(es)	None	
DOT	Not applicable	
Packing group		
DOT	Not applicable	
Environmental hazards:		
Marine pollutant:	No	

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

• Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

68081-81-2 Sodium Dodecyl Benzene Sulfonate

66455-15-0 C10-12 6 Mole Linear Alcohol Ethoxylate

57-55-6 propane-1,2-diol

68648-87-3 Benzene C-10-16 Alkylate

(Contd. on page 7)

(Contd. of page 5)

USA -

Printing date 12/30/2014

Reviewed on 03/19/2014

(Contd. of page 6)

Trade name: Tire Lubricant

//3/-82-0	sodium sulphate
4719-04-4	2,2',2"-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol

7732-18-5 water, distilled, conductivity or of similar purity

· Proposition 65

7757 02 (

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicalsknown to cause reproductive toxicity for males.

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Warning

- *Hazard-determining components of labeling:* Sodium Dodecyl Benzene Sulfonate
- · Hazard statements
- Causes serious eye irritation.
- · Precautionary statements

If medical advice is needed, have product container or label at hand.

- Keep out of reach of children.
- Read label before use.

Wear protective gloves/protective clothing/eye protection/face protection.

Wash thoroughly after handling.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 8)

Printing date 12/30/2014

Reviewed on 03/19/2014

Trade name: Tire Lubricant

	(Contd. of page 7)
Department issuing MSDS: Environment protection department.	
Date of preparation / last revision	
12/30/2014 / -	
Revised 6/6/2014 to DDBSA sodium salt base.	
Abbreviations and acronyms:	
IMDG: International Maritime Code for Dangerous Goods	
DOT: US Department of Transportation	
IATA: International Air Transport Association	
ACGIH: American Conference of Governmental Industrial Hygienists	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, EU)	
Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A	
	USA