

PowerKleen
Quality Chemicals • Superior Service

Directions:

Apply diluted solution freely to floor and allow floor to dry. It may be necessary in stubborn cases to scrub with brush, pad, or steel wool. Old finish and soil can be easily removed from floors using squeegee, or vacuum. Mop entire surface with clean mop to remove all foreign material before applying new floor finish.

- **For normal build up:** use 12 ounces of stripper per gallon of warm water.
- **For heavy build up:** use 20 ounces per gallon of warm water.

DANGER:

DO NOT TAKE INTERNALLY. HARMFUL IF SWALLOWED.

CAUTION: KEEP OUT OF REACH OF CHILDREN.

MAY CAUSE HARM TO PAINTED SURFACES IF NOT USED AS DIRECTED

Non-Ammoniated Stripper

STRIPS QUICKLY AND EASILY

PROFESSIONAL-GRADE FLOOR STRIPPER

QUICKLY STRIPS & CLEANS ALL POLYMER AND ACRYLIC FLOOR FINISHES FROM ALL TYPES OF COMPOSITION FLOOR TILE, CONCRETE, TERRAZZO, VINYL AND LINOLEUM.

1 Gal.

5 Gal.

55 Gal.

275 Gal.



CORROSIVE

8

Inhalation: Remove affected person to fresh air; wash mouth and nasal passages with water repeatedly; if breathing difficulties persist seek medical attention.

Skin: Remove contaminated clothing; wash affected area with soap and water; DO NOT attempt to neutralize with chemical agents; if irritation persists, seek medical attention. Launder contaminated clothing before reuse.

Eyes: Check for and remove any contact lenses. Immediately flush eyes with clear running water for 15 minutes while holding eyelids open. Seek medical attention immediately.

Ingestion: Drink two glasses of water followed by milk; give diluted vinegar or lemon juice to conscious person; DO NOT induce vomiting; seek medical attention immediately.

PowerKleen

Quality Chemicals • Superior Service

Power Kleen Corporation
To Reorder, Call: (813) 854-2648
FAX (813) 854-3133

In Case Of Chemical Emergency Contact
Chem-Tel 24 Hours (800) 255-3924

www.PowerKleen.com

TRANSPORT INFORMATION:

Proper Shipping Name -

Corrosive Liquids, N.O.S.,

(Contains Potassium Hydroxide)

DOT Hazard Class - 8 Packing Group - III

ID# - UN 1760