Printing date 10/27/2014

Reviewed on 02/12/2014

| 1 Identification | |
|--|---|
| 1 Identification | |
| · Product identifier | |
| · Trade name: <u>Bell Wash</u> | Jamson Labs Power Kleen |
| • Article number: 6530 PK | Chemical Solutions Since 1973 |
| • Details of the supplier of the safety data sheet • Manufacturer/Supplier: Power Kleen Corporation 101 South Bayview Blvd. OLDSMAR, FL 34677 USA | Chemical Solutions Shee 1775 |
| • Information department: Product Safety Department • Emergency telephone number: ChemTel Inc. (800) 25 | 5-3924 Intl. +01 (813) 248-0585 |
| 2 Hazard(s) identification | |
| · Classification of the substance or mixture | |
| Classification of the substance of mixture | |
| GHS05 Corrosion | |
| Skin Corr. 1B H314 Causes severe skin burns and ey | e damage. |
| Eye Dam. 1 H318 Causes serious eye damage. | |
| Label elements GHS label elements The product is classified and labe Hazard pictograms | led according to the Globally Harmonized System (GHS). |
| | |
| GHS05 | |
| · Signal word Danger | |
| · Hazard-determining components of labeling: | |
| disodium metasilicate • Hazard statements | |
| Causes severe skin burns and eye damage. | |
| • Precautionary statements If medical advice is needed, have product container or | label at hand |
| Keep out of reach of children. | |
| Read label before use. | |
| Do not breathe dust/fume/gas/mist/vapours/spray. IF ON SKIN (or hair): Remove/Take off immediately a | ll contaminated clothing. Rinse skin with water/shower. |
| | minutes. Remove contact lenses, if present and easy to do. |
| Continue rinsing. | · - |
| Specific treatment (see on this label). Store locked up. | |
| Dispose of contents/container in accordance with loca | l/regional/national/international regulations. (Contd. on page 2) USA — |

(Contd. of page 1)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/27/2014

Reviewed on 02/12/2014

Trade name: Bell Wash

| · Classification system: |
|------------------------------|
| · NFPA ratings (scale 0 - 4) |

Health = 3Fire = 0 Reactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTH3Health = 3FIRE0Fire = 0REACTIVITY0Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

| · Dangerous components: | | |
|-------------------------|---|---------------|
| 6834-92-0 | disodium metasilicate | 2.5-10% |
| 66455-15-0 | C10-12 6 Mole Linear Alcohol Ethoxylate | <i>≤</i> 2.5% |
| 111-76-2 | 2-butoxyethanol | ≤ 2.5% |
| 67-63-0 | propan-2-ol | <i>≤</i> 2.5% |

4 First-aid measures

· Description of first aid measures

• General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Remove contact lenses if able to do so.

Rinse opened eye for several minutes under running water. Then consult a doctor.

- · After swallowing:
- Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

· Most important symptoms and effects, both acute and delayed

Nausea

Corrosive and extremely irritating to all tissues.

Cramp

Gastric or intestinal disorders

• **Danger** Danger of gastric perforation.

(Contd. on page 3)

USA

Printing date 10/27/2014

Reviewed on 02/12/2014

Trade name: Bell Wash

• Indication of any immediate medical attention and special treatment needed Medical supervision for at least 48 hours.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 Environmental precautions:
- Dilute with plenty of water.
- Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent.
- Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.
- **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- · Information about protection against explosions and fires: No special measures required.
- \cdot Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Unsuitable material for receptacle: aluminium.
- · Information about storage in one common storage facility:
- Store away from oxidizing agents. Store away from foodstuffs.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

(Contd. of page 2)

USA

Printing date 10/27/2014

Reviewed on 02/12/2014

Trade name: Bell Wash

| - Components with values that require monitoring at the workplace: - III-76-2 2-butoxyethanol PEL Long-term value: 240 mg/m², 50 ppm Skin REL Long-term value: 97 mg/m², 20 ppm BEI - G7-63-0 propan-2-ol PEL Long-term value: 980 mg/m², 400 ppm Long-term value: 980 mg/m², 400 ppm REL Stort-term value: 926 mg/m², 20 ppm BEI - G7-63-0 propan-2-ol PEL Long-term value: 980 mg/m², 400 ppm Long-term value: 980 mg/m², 400 ppm REL Stort-term value: 920 mg/m², 200 ppm BEI - G7-63-0 propan-2-ol PEL Long-term value: 980 mg/m², 400 ppm Long-term value: 980 mg/m², 400 ppm REL Stort-term value: 980 mg/m², 400 ppm Long-term value: 980 mg/m², 400 ppm Long-term value: 980 mg/m², 200 ppm BEI - Ingredients with biological limit values: III-76-2 2-butoxyethanol BEI - Mg/e creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis - G7-63-0 propan-2-ol BEI - Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis - G7-63-0 propan-2-ol BEI - Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis - G7-63-0 propan-2-ol BEI - Medium: urine Time: end of shift end of workweek Parameter: Acetone (background, nonspecific) - Additional Information: The lists that were valid during the creation were used as basis Exposure controls - Reprosentation: The lists that were valid during the creation were used as basis Stopestic equipment: In case of bift equipm | | (Contd. of page 3) |
|---|------------------------|---|
| 111-76-2 2-butoxyethanol PEL Long-term value: 240 mg/m ³ , 50 ppm Skin REL Long-term value: 24 mg/m ³ , 50 ppm Skin REL Long-term value: 97 mg/m ³ , 20 ppm BEI C763-0 propan-2-01 PEL Long-term value: 1225 mg/m ³ , 400 ppm Long-term value: 1225 mg/m ³ , 400 ppm Long-term value: 920 mg/m ³ , 400 ppm Long-term value: 920 mg/m ³ , 200 ppm Long-term value: 920 mg/m ³ , 200 ppm BEI Of Mg/L Medium: urine Time-end of shift Parameter: Butoxyacetic acid with hydrolysis 67-63-0 propan-2-01 BEI Parameter: Acetone (background, nonspecific) Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective equipment: In case of brief exposure or low polution use respiratory filter device. In case of intensive or longe | | |
| PEL Long-term value: 240 mg/m ¹ , 50 ppm Skin REL Long-term value: 24 mg/m ² , 5 ppm Skin TIV Long-term value: 97 mg/m ¹ , 20 ppm BEL Long-term value: 97 mg/m ¹ , 20 ppm BEL Long-term value: 980 mg/m ¹ , 400 ppm LONG-term value: 1225 mg/m ¹ , 400 ppm Long-term value: 980 mg/m ¹ , 400 ppm Long-term value: 982 mg/m ¹ , 400 ppm BEI 40 mg/L Medium: urine < | | · · · · · |
| Star Star REL Long-term value: 24 mg/m ¹ , 50 ppm Star Long-term value: 22 mg/m ¹ , 400 ppm BEI Core-term value: 1225 mg/m ¹ , 400 ppm REL Long-term value: 225 mg/m ¹ , 500 ppm Long-term value: 980 mg/m ¹ , 400 ppm Long-term value: 980 mg/m ¹ , 400 ppm Long-term value: 980 mg/m ¹ , 400 ppm Long-term value: 984 mg/m ¹ , 200 ppm Long-term value: 980 mg/m ¹ , 400 ppm Long-term value: 984 mg/m ¹ , 200 ppm BEI Start-term value: 984 mg/m ¹ , 200 ppm BEI Start Redium: urine Time: end of shift Parameter: Sutoxyacetic acid with hydrolysis 67-63-0 propan-2-01 BEI Medium: urine Medium: urine Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Personal protective equipment: • General protective and hgienic measures: Kovid contact with the eyes. Avoid contact with the eyes. Avoid contact with the eyes. Novid contact wit | | · · · · · · |
| Skin Skin TUV Long-term value: 97 mg/m³, 20 ppm BEI 67-63-0 propan-2-ol PEL Long-term value: 980 mg/m³, 400 ppm REL Short-term value: 925 mg/m³, 500 ppm Long-term value: 984 mg/m³, 200 ppm Engedients with biological limit values: III-76-22-butoxyethanol BEI BEI Om g/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis 67-63-0 propan-2-ol BEI Modium: urine Time: end of shift at end of workweek Parameter: Actone (background, nonspecific) Parameter: Actone (background, nonspecific) Parameter: Actone (background, nonspecific) Personal protective equipment: General protective equipment: "General protective equipment: General protective equipment: "General protective equipment: Novid contact with the eyes and skin. "Immediately remove all solied and contaminated clothing. Wash hands before breaks and feed. Movid contact with the eyes and skin. The store of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protective gloves Protective glovese <td>PEL</td> <td></td> | PEL | |
| BEI 67-63-0 progan-2-0 FEL Long-term value: 980 mg/m³, 400 ppm Long-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm TLV Short-term value: 492 mg/m³, 200 ppm BEI Ong-term value: 492 mg/m³, 200 ppm BEI 200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis 67-63-0 progan-2-ol BEI 400 mg/L Medium: urine Time: end of shift and of workweek Parameter: Acctone (background, nonspecific) - Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: 'General protective equipment: 'Wash hands before breaks and at the end of work. Avoid contact with the eyes: Avoid contact with the eyes and skin. Breating equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protective gloves Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation | REL | |
| PEL Long-term value: 980 mg/m ³ , 400 ppm REL Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm Long-term value: 984 mg/m ³ , 400 ppm Long-term value: 982 mg/m ³ , 400 ppm BEI 111-76-2 2-butoxyethanol BEI 200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis 67-63-0 propan-2-ol BEI 40 mg/l. Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific) - Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective and hygienic measures: Keep avox from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. Breathing equipment: In case of brie | TLV | |
| REL Short-term value: 1225 mg/m ¹ , 500 ppm Long-term value: 980 mg/m ¹ , 400 ppm Long-term value: 980 mg/m ¹ , 200 ppm BE ITV Short-term value: 992 mg/m ¹ , 200 ppm BEI Ingredients with biological limit values: III-76-2 3-butoxyethanol BEI Dom marks with biological limit values: III-76-2 3-butoxyethanol BEI Dom marks with biological limit values: III-76-2 3-butoxyethanol BEI Dom marks with biological limit values: III-76-2 3-butoxyethanol BEI Dom marks with biological limit values: Time: end of shift Parameter: Butoxyacetic acid with hydrolysis 67-63-0 propan-2-ol BEI BU Medium: urine Time: end of shift at end of workweek Parameter: Actome (background, nonspecific) - Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective and hygeine measures: Kee avoay from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and athe end of work. | 67-6 | 3-0 propan-2-ol |
| Long-term value: 980 mg/m², 400 ppm I. Short-term value: 984 mg/m², 400 ppm Long-term value: 492 mg/m², 200 ppm BEI Ingredients with biological limit values: 1117-6-2 3-butoxyethanol BEI 200 mg/g creatinine Medium: wrine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis 67-63-0 propan-2-ol BEI 40 mg/L Medium: wrine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls Personal protective equipment: • General protective equipment: • General protective equipment: • General protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. • Treathing equipment In case of brief exposure or low pollution use resp | PEL | Long-term value: 980 mg/m ³ , 400 ppm |
| Long-term value: 492 mg/m³, 200 ppm BEI Ingredients with biological limit values: 1117-62-2-butoxyethanol BEI 200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis 67-63-0 propan-2-ol BEI 40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective equipment: • General protective and hygienic measures: Keep away from foodstiffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: Wealection of thands: Extend away fo | REL | |
| Ingredients with biological limit values: III-76-2 2-butoxyethanol BEI 200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis 67-63-0 propan-2-ol BEI 40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific) Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective equipment: General protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes. Protentiar With the eyes. Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Matriar of gloves Procentiar of playes Neoprene gloves (Contd. on page 5) | TLV | Long-term value: 492 mg/m ³ , 200 ppm |
| 111-76-2 2-butoxyethanol BEI 200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis 67-63-0 propan-2-ol BEI 40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes. Avoid contact with the eyes. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: Were anterial has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material no consideration of the penetration times, rates of diffusion and the degradation • Material of gloves PVC or PE gloves | | |
| BEI 200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis 67-63-0 propan-2-ol BEI 40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: • Protection of hands: • Develotive gloves • The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves PVC or PE gloves | - | |
| Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis 67-63-0 propan-2-ol BEI 40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure of low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: word Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves PVC or PE gloves <td></td> <td>-</td> | | - |
| Time: end of shift Parameter: Butoxyacetic acid with hydrolysis 67-63-0 propan-2-ol BEI 40 mg/L. Medium: wrine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: Worker all has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves PVC or PE gloves | BEI | |
| Parameter: Butoxyacetic acid with hydrolysis 67-63-0 propan-2-ol BEI 40 mg/L. Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: <i>Work Notactive gloves Naterial of gloves Naterial of gloves Neoprene gloves Neoprene gloves Neoprene gloves</i> | | |
| BEI 40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: <i>Work Material has to be impermeable and resistant to the product/ the substance/ the preparation.</i> Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation <i>Material of gloves</i> Neoprene gloves PVC or PE gloves | | |
| Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: • Protective gloves Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves Wor or Egloves | 67-6 | 3-0 propan-2-ol |
| Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: • Difference • Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves PC or PE gloves | BEI | 40 mg/L |
| Parameter: Acetone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: • Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves Neoprene gloves PVC or PE gloves | | |
| Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves PVC or PE gloves (Contd. on page 5) | | |
| Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. Freathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the gloves material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves Neoprene gloves (Contd. on page 5) | | |
| Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the gloves material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves Neoprene gloves VC or PE gloves | • Addi | itional information: The lists that were valid during the creation were used as basis. |
| General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the gloves Material of gloves Neoprene gloves (Contd. on page 5) | | |
| Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves Neoprene gloves (Contd. on page 5) | | |
| Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves Neoprene gloves (Contd. on page 5) | | |
| Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves Neoprene gloves (Contd. on page 5) | | |
| Avoid contact with the eyes. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves Neoprene gloves (Contd. on page 5) | | |
| Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves Neoprene gloves PVC or PE gloves (Contd. on page 5) | | |
| In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: • Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves Neoprene gloves PVC or PE gloves (Contd. on page 5) | | |
| respiratory protective device that is independent of circulating air. Protection of hands: <i>Protective gloves</i> <i>Protective gloves</i> The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves Neoprene gloves PVC or PE gloves | | |
| Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves Neoprene gloves PVC or PE gloves | | |
| Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves Neoprene gloves PVC or PE gloves (Contd. on page 5) | - | |
| The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves Neoprene gloves PVC or PE gloves (Contd. on page 5) | 1100 | ection of nanas. |
| Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves Neoprene gloves PVC or PE gloves (Contd. on page 5) | UNIT | Protective gloves |
| PVC or PE gloves (Contd. on page 5) | Selec • Mate | ction of the glove material on consideration of the penetration times, rates of diffusion and the degradation erial of gloves |
| (Contd. on page 5) | | |
| | | (Contd. on page 5) |

Printing date 10/27/2014

Reviewed on 02/12/2014

Trade name: Bell Wash

(Contd. of page 4)

Butyl rubber, BR Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. • Penetration time of glove material

- The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Not suitable are gloves made of the following materials: Strong gloves Leather gloves

• Eye protection:



Tightly sealed goggles

· Body protection: Alkaline resistant protective clothing

| Information on basic physical and | chemical properties | |
|-----------------------------------|---|--|
| General Information | | |
| Appearance: | | |
| Form: | Liquid | |
| Color: | Blue | |
| Odor: | Characteristic | |
| Odour threshold: | Not determined. | |
| pH-value at 20 °C (68 °F): | 13 | |
| Change in condition | | |
| Melting point/Melting range: | Undetermined. | |
| Boiling point/Boiling range: | 100 °C (212 °F) | |
| Flash point: | Not applicable. | |
| Flammability (solid, gaseous): | Not applicable. | |
| Ignition temperature: | | |
| Decomposition temperature: | Not determined. | |
| Auto igniting: | Product is not selfigniting. | |
| Danger of explosion: | Product does not present an explosion hazard. | |
| Explosion limits: | | |
| Lower: | Not determined. | |
| Upper: | Not determined. | |
| Vapor pressure: | Not determined. | |
| Density at 20 °C (68 °F): | 1.03 g/cm ³ (8.595 lbs/gal) | |
| Relative density | Not determined. | |
| Vapour density | Not determined. | |
| Evaporation rate | Not determined. | |

USA

Printing date 10/27/2014

Reviewed on 02/12/2014

Trade name: Bell Wash

| | | (Contd. of page |
|----------------------------------|--|-----------------|
| Solubility in / Miscibility with | | |
| Water: | Fully miscible. | |
| Partition coefficient (n-octan | ol/water): Not determined. | |
| Viscosity: | | |
| Dynamic: | Not determined. | |
| Kinematic: | Not determined. | |
| Solvent content: | | |
| Organic solvents: | 1.9~% | |
| Water: | 88.7 % | |
| VOC content: | 1.9~% | |
| | 32.4 g/l / 0.27 lb/gl | |
| Solids content: | 9.4 % | |
| Other information | No further relevant information available. | |

10 Stability and reactivity

· Reactivity

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Reacts with strong acids and oxidizing agents.
- · Conditions to avoid No further relevant information available.
- *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- \cdot on the eye:
- Strong caustic effect.
- Strong irritant with the danger of severe eye injury.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

- Corrosive
- Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

| · IARC (International Agency for Research on Cancer) | |
|--|--------------------|
| 111-76-2 2-butoxyethanol | 3 |
| 67-63-0 propan-2-ol | 3 |
| · NTP (National Toxicology Program) | |
| None of the ingredients is listed. | |
| | (Contd. on page 7) |

Printing date 10/27/2014

Reviewed on 02/12/2014

Trade name: Bell Wash

(Contd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · *Bioaccumulative potential* No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

- Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- Danger to drinking water if even extremely small quantities leak into the ground.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- *Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

| · UN-Number | |
|------------------------------|--|
| · DOT, IMDG, IATA | UN3266 |
| · UN proper shipping name | |
| $\cdot DOT$ | Corrosive liquid, basic, inorganic, n.o.s. (Sodium hydroxide |
| | Disodium trioxosilicate) |
| · IMDG | CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (SODIUM |
| | HYDROXIDE, DISODIUM TRIOXOSILICATE), MARINI |
| | POLLUTANT |
| ·IATA | CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (SODIUM |
| | HYDROXIDE, DISODIUM TRIOXOSILICATE) |
| · Transport hazard class(es) | |
| · DOT, IMDG, IATA | |
| · Class | 8 Corrosive substances |

Printing date 10/27/2014

Reviewed on 02/12/2014

Trade name: Bell Wash

| | (Contd. of page 2 |
|--|---|
| · Label | 8 |
| · Packing group | |
| · DOT, IMDG, IATA | III |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | |
| · Danger code (Kemler): | 80 |
| · EMS Number: | F- A , S - B |
| · Segregation groups | Alkalis |
| · Transport in bulk according to Annex | II of |
| MARPOL73/78 and the IBC Code | Not applicable. |
| • UN "Model Regulation": | UN3266, Corrosive liquid, basic, inorganic, n.o.s. (Sodiun hydroxide, Disodium trioxosilicate), ENVIRONMENTALLY HAZARDOUS, 8, III |

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

| None of the | ingredients is listed. |
|------------------|---|
| Section 313 | (Specific toxic chemical listings): |
| 111-76-2 | 2-butoxyethanol |
| 67-63-0 | propan-2-ol |
| 7758-29-4 | pentasodium triphosphate |
| 67-56-1 | methanol |
| TSCA (Tox | ic Substances Control Act): |
| 6834-92-0 | disodium metasilicate |
| 66455-15-0 | C10-12 6 Mole Linear Alcohol Ethoxylate |
| 111-76-2 | 2-butoxyethanol |
| 67-63-0 | propan-2-ol |
| 7758-29-4 | pentasodium triphosphate |
| 68604-71-7 | Disodium cocoamphodipropionate |
| 64-02-8 | tetrasodium ethylenediaminetetraacetate |
| 67-56-1 | methanol |
| 7732-18-5 | water, distilled, conductivity or of similar purity |
| Proposition | |
| Chemicals i | known to cause cancer: |
| None of the | ingredients is listed. |
| Chemicals | known to cause reproductive toxicity for females: |
| None of the | ingredients is listed. |
| Chemicalsk | nown to cause reproductive toxicity for males. |
| None of the | ingredients is listed. |

Printing date 10/27/2014

Reviewed on 02/12/2014

Trade name: Bell Wash

(Contd. of page 8)

NL

A3

A4

 \cdot Chemicals known to cause developmental toxicity:

67-56-1 methanol

· Carcinogenic categories

· EPA (Environmental Protection Agency)

111-76-2 2-butoxyethanol

· TLV (Threshold Limit Value established by ACGIH)

111-76-2 2-butoxyethanol

67-63-0 propan-2-ol

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

• Hazard-determining components of labeling: disodium metasilicate

• *Hazard statements Causes severe skin burns and eye damage.*

Precautionary statements
If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read label before use.
Do not breathe dust/fume/gas/mist/vapours/spray.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Specific treatment (see on this label).
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing MSDS: Environment protection department.

- · Date of preparation / last revision
- 10/27/2014 / -02/12/2014

 Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

(Contd. on page 10)

[•] USA

Printing date 10/27/2014

Reviewed on 02/12/2014

Trade name: Bell Wash

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 (Contd. of page 9)

USA